FLANGE SEALANT - ANAEROBIC LP



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 29.09.2021 **REVISION DATE: 06.01.2023** SUPERSEDES: 29.09.2021

VERSION: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: Flange Sealant - Anaerobic LP Trade name Product code : Ford Internal Ref .: 502529

SDS Number : 8873

UFI : CCRV-AEVG-E10Y-VTSD

Product use : Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Adhesives, sealants

1.2.2. Uses advised against

Restrictions on use : None known

1.3. Details of the supplier of the safety data sheet

Supplier Distributor

Ford-Werke GmbH Ford Motor Company Ltd. Edsel-Ford-Str. 2-14 Parts Distribution Centre 50769 Cologne Royal Oak Way South Germany NN11 8NT Daventry, Northants

+49 221 90-33333 United Kingdom +44 1327 305 198 sdseu@ford.com

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Health hazards Serious eye damage/eye irritation, H319 Causes serious eye irritation.

Category 2

Skin sensitisation, Category 1 H317 May cause an allergic skin reaction. Specific target organ toxicity - Single H335 May cause respiratory irritation.

exposure, Category 3, Respiratory tract

Environmental hazards Hazardous to the aquatic environment - H410 Very toxic to aquatic life with long lasting effects.

Chronic Hazard, Category 1

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms





Signal word Warning

Contains α,α-dimethylbenzyl hydroperoxide ; 2-Phenylacetohydrazide; 1,1'-(methylenedi-p-

phenylene)bismaleimide

Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P261 Avoid breathing vapours.
P273 Avoid release to the environment.
P280 Wear eye protection, protective gloves.

Response

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Other hazards which do not result in classification : This product contains a substance that is classified as Acute Toxicity Category 3, Inhalation, in

powder form. Experimental data show that this substance, as an ingredient in this mixture, is not

biologically available according to CLP Art. 12 b.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
1,1'-(methylenedi-p-phenylene)bismaleimide	13676-54-5 237-163-4 - 01-2119969947-11-XXXX	1 - < 10	Acute Tox. 3 (Inhalation), H331 (ATE=0.515 mg/l/4h) Skin Sens. 1, H317 Aquatic Chronic 1, H410 (M=10)	
α,α-dimethylbenzyl hydroperoxide	80-15-9 201-254-7 617-002-00-8 01-2119475796-19-XXXX	1 -< 2	Org. Perox. E, H242 Acute Tox. 3 (Inhalation), H331 (ATE=3 mg/l/4h) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight)	(0 ≤C ≤ 10) STOT SE 3, H335 (1 ≤C ≤ 3) Eye Irrit. 2, H319 (3 ≤C ≤ 10) Skin Irrit. 2, H315 (3 ≤C ≤ 10) Eye Dam. 1, H318 (10 ≤C ≤ 100) Skin Corr. 1B, H314

			STOT RE 2, H373	
			Skin Corr. 1B, H314	
			Aquatic Chronic 2, H411	
2-Phenylacetohydrazide	114-83-0	0,1 -< 1	Acute Tox. 3 (Oral), H301	
	204-055-3		(ATE=100 mg/kg	
	-		bodyweight)	
			Skin Irrit. 2, H315	
			Eye Irrit. 2, H319	
			Skin Sens. 1, H317	
			Carc. 2, H351	
			STOT SE 3, H335	
3,6-bis(ethylamino)-9-[2-	3068-39-1	0,01 - <	Acute Tox. 4 (Oral), H302	
(methoxycarbonyl)phenyl]-2,7-	221-326-1	0,1	(ATE=500 mg/kg	
dimethylxanthylium chloride	-		bodyweight)	
	01-2120107344-68		Acute Tox. 2	
			(Inhalation:dust,mist), H330	
			(ATE=0.05 mg/l/4h)	
			Eye Dam. 1, H318	
			Skin Sens. 1B, H317	
			Aquatic Chronic 1, H410	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Never give anything by mouth to

an unconscious person.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if

you feel unwell.

First-aid measures after skin contact : Wash skin with soap and water. Take off contaminated clothing. If skin irritation or rash occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes

minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

ophtalmologist if irritation persists.

First-aid measures after ingestion : Call a physician immediately. Rinse mouth out with water. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation. May cause shortness of breath, tightness of the chest, a sore throat

and cough.

Symptoms/effects after skin contact : May cause an allergic skin reaction. Skin rash/inflammation.

Symptoms/effects after eye contact : Eye irritation. Conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO2). Nitrogen oxides.

Sulphur oxides.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Keep unnecessary personnel away. Move

containers from fire area if it can be done without personal risk.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to

section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

For containment : Waste disposal recommendations.

Methods for cleaning up : Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is

possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Take up liquid spill into absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills in original containers for

re-use.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin and

eyes. Wear personal protective equipment.

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas.

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible products : Strong acids. Strong oxidizing agent. Keep away from open flames, hot surfaces and sources of

ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

Adhesives, sealants.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Propane-1,2-diol (57-55-6)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1] 10 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

α,α-dimethylbenzyl hydroperoxide (80-15-9)

DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation 6 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0.003 mg/l

PNEC aqua (marine water) 0 mg/l

PNEC aqua (intermittent, freshwater) 0.031 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 0.023 mg/kg dwt

PNEC sediment (marine water) 0.002 mg/kg dwt

PNEC (Soil)

PNEC soil 0.003 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 0.35 mg/l

3,6-bis(ethylamino)-9-[2-(methoxycarbonyl)phenyl]-2,7-dimethylxanthylium chloride (3068-39-1)

DNEL/DMEL (Workers)

Acute - systemic effects, dermal 0.25 mg/cm³

Long-term - systemic effects, dermal 0.02 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 0.06 mg/kg KW

Long-term - local effects, inhalation 0.125 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0 mg/l

PNEC aqua (marine water) 0 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 0.989 mg/kg dwt

PNEC sediment (marine water) 0.099 mg/kg dwt

PNEC (Soil)

PNEC soil 0.198 mg/kg dwt

PNEC (Oral)

PNEC oral (secondary poisoning) 0.1 mg/kg food

PNEC (STP)

PNEC sewage treatment plant 0.33 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eve protection:

EN 166. Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. EN 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Type A - High-boiling (>65 °C) organic compounds

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : pink. Appearance : gel. Odour : mild. Odour threshold : Not available Melting point : Not applicable : Not available Freezing point : > 150 °C Boiling point Flammability : Not applicable **Explosive limits** : Not available Lower explosive limit (LEL) : Not available : Not available Upper explosive limit (UEL) : > 93.3 °C Flash point Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available Viscosity, kinematic : Not available

Solubility : Water solubility. Slightly soluble.

Log Kow : Not available
Vapour pressure : < 5 mm Hg @ 27°C

Vapour pressure at 50°C : < 300 mbar : 1.178 g/cm³ Density : Not available Relative density Relative vapour density at 20°C : Not available : Not applicable Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio Particle aggregation state : Not applicable : Not applicable Particle agglomeration state : Not applicable Particle specific surface area Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 3 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Germ cell mutagenicity

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2). During fire, gases hazardous to health may be formed. Nitrogen oxides. Sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)

Based on available data, the classification criteria are not met

Cute toxicity (dermal)

Based on available data, the classification criteria are not met

Cute toxicity (inhalation)

Based on available data, the classification criteria are not met

Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met	
α,α-dimethylbenzyl hydroperoxide (80-15-9)		
LD50 oral rat	382 mg/kg bodyweight	
3,6-bis(ethylamino)-9-[2-(methoxycarbonyl)phenyl]-2,7-dimethylxanthylium chloride (3068-39-1)		
LC50 Inhalation - Rat	515 mg/l	
1,1'-(methylenedi-p-phenylene)bismaleimide (13676-54-5)		
LD50 oral rat	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat (Dust/Mist)	0.515 – 1 mg/l/4h	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	

: Based on available data, the classification criteria are not met

Carcinogenicity : Based on available data, the classification criteria are not met Reproductive toxicity : Based on available data, the classification criteria are not met

STOT-single exposure : May cause respiratory irritation.

2-Phenylacetohydrazide (114-83-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Based on available data, the classification criteria are not met

α,α-dimethylbenzyl hydroperoxide (80-15-9)

Aspiration hazard : Based on available data, the classification criteria are not met

11.2. Information on other hazards

No additional information available

STOT-repeated exposure

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Based on available data, the classification criteria are not met

May cause damage to organs through prolonged or repeated exposure.

: Very toxic to aquatic life with long lasting effects.

1,1'-(methylenedi-p-phenylene)bismaleimide (13676-54-5)

LC50 - Fish [1]	> 145 μg/l
EC50 - Crustacea [1]	> 99.4 µg/l
EC50 72h - Algae [1]	> 0.135 mg/l

12.2. Persistence and degradability

1,1'-(methylenedi-p-phenylene)bismaleimide (13676-54-5)

ThOD 0.05 g O2/I @ 28 d

12.3. Bioaccumulative potential

α, α -dimethylbenzyl hydroperoxide (80-15-9)

Log Pow 1.6

12.4. Mobility in soil

1,1'-(methylenedi-p-phenylene)bismaleimide (13676-54-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)

12.5. Results of PBT and vPvB assessment

Flange Sealant - Anaerobic LP

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Dispose of in accordance with local regulations.

Waste treatment methods : Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions). Collect and reclaim or dispose in closed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose of contents/container in accordance with

licensed collector's sorting instructions.

Sewage disposal recommendations : Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds,

waterways or ditches with chemical or used container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

 UN-No. (ADR)
 : UN 3082

 UN-No. (IMDG)
 : UN 3082

 UN-No. (IATA)
 : UN 3082

 UN-No. (ADN)
 : UN 3082

 UN-No. (RID)
 : UN 3082

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,1'-(methylenedi-p-

phenylene)bismaleimide)

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,1'-(methylenedi-p-

phenylene)bismaleimide)

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (1,1'-(methylenedi-p-phenylene)bismaleimide)

Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,1'-(methylenedi-p-

phenylene)bismaleimide)

Proper Shipping Name (RID) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,1'-(methylenedi-p-

phenylene)bismaleimide)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 9
Danger labels (ADR) : 9

IMDG

Transport hazard class(es) (IMDG) : 9
Danger labels (IMDG) : 9

IATA

Transport hazard class(es) (IATA) : 9
Hazard labels (IATA) : 9

ADN

Transport hazard class(es) (ADN) : 9
Danger labels (ADN) : 9

RID

Transport hazard class(es) (RID) : 9
Danger labels (RID) : 9

14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes

Other information : No supplementary information available.

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I

Packing instructions (ADR) : P001, IBC03, LP01, R001

Hazard identification number (Kemler No.) : 90
Tunnel restriction code (ADR) : EAC code : •3Z

Transport by sea

Special provisions (IMDG): 274, 335, 969Limited quantities (IMDG): 5 LPacking instructions (IMDG): LP01, P001EmS-No. (Fire): F-AEmS-No. (Spillage): S-FStowage category (IMDG): A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L
Carriage permitted (ADN) : T

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L

Packing instructions (RID) : P001, IBC03, LP01, R001

Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
• ()	

 α, α -dimethylbenzyl hydroperoxide

3(b) Flange Sealant - Anaerobic LP; α,α-dimethylbenzyl hydroperoxide; 2-Phenylacetohydrazide

3(c) Flange Sealant - Anaerobic LP ; α,α-dimethylbenzyl hydroperoxide

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : < 3 %

Other information, restriction and prohibition regulations : Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently

given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

Seveso III Part I (Categories of dangerous substances)

Qualifying quantity (tonnes)

	Lower-tier	Upper-tier	
E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200	

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section 3. Composition/information on ingredients. Section 2. Label elements.

Abbreviations and acronyms

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Bioconcentration factor
BLV Biological limit value

BOD Biochemical oxygen demand (BOD)
COD Chemical oxygen demand (COD)
DMEL Derived Minimal Effect level
DNEL Derived-No Effect Level
EC-No. European Community number
EC50 Median effective concentration

EN European Standard

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Median lethal concentration LD50 Median lethal dose

LOAEL Lowest Observed Adverse Effect Level
NOAEC No-Observed Adverse Effect Concentration

NOAEL No-Observed Adverse Effect Level NOEC No-Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

OEL Occupational Exposure Limit

PBT Persistent Bioaccumulative Toxic

PNEC Predicted No-Effect Concentration

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS Safety Data Sheet
STP Sewage treatment plant

ThOD Theoretical oxygen demand (ThOD)

TLM Median Tolerance Limit

VOC Volatile Organic Compounds

CAS-No. Chemical Abstract Service number

N.O.S. Not Otherwise Specified

vPvB Very Persistent and Very Bioaccumulative

ED Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of

16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC)

No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Acute Tox. 2 Acute toxicity (inhalation:dust,mist) Category 2

(Inhalation:dust,mist)

Acute Tox. 3 (Inhalation)

Acute toxicity (inhal.), Category 3

Acute Tox. 3 (Oral)

Acute toxicity (oral), Category 3

Acute Tox. 4 (Dermal)

Acute toxicity (dermal), Category 4

Acute Tox. 4 (Oral)

Acute toxicity (oral), Category 4

Aquatic Chronic 1 Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2 Hazardous to the aquatic environment – Chronic Hazard, Category 2

Carc. 2 Carcinogenicity, Category 2

Eye Dam. 1 Serious eye damage/eye irritation, Category 1
Eye Irrit. 2 Serious eye damage/eye irritation, Category 2

H242 Heating may cause a fire.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H330 Fatal if inhaled. H331 Toxic if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

Org. Perox. E Organic Peroxides, Type E

Skin Corr. 1B Skin corrosion/irritation, Category 1, Sub-Category 1B

Skin Irrit. 2 Skin corrosion/irritation, Category 2
Skin Sens. 1 Skin sensitisation, Category 1
Skin Sens. 1B Skin sensitisation, category 1B

STOT RE 2 Specific target organ toxicity – Repeated exposure, Category 2

STOT SE 3 Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Eye Irrit. 2H319Calculation methodSkin Sens. 1H317Calculation methodSTOT SE 3H335Calculation methodAquatic Chronic 1H410Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Attachment to the Safety Data Sheet

Product Name: Flange Sealant - Anaerobic LP

Ford Int. Ref. No.: 502529 Revision Date: 06.01.2023

Involved Products:

Finiscode Part number Container Size:

1 2 550 017 5U7J M2G348 CA 50 ml