

CLINCHED FLANGE SEALER



SAFETY DATA SHEET

according to Regulation (EU) 2015/830

ISSUE DATE: 18.07.2014

REVISION DATE: 13.03.2017

SUPERSEDES DATE: 18.07.2014

VERSION: 3.0

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	Clinched Flange Sealer
Product code	Ford Internal Ref: 102972
SDS Number	8046
Product use	Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Adhesives, binding agents
Uses advised against	No additional information available.

1.3. Details of the supplier of the safety data sheet

Supplier	Distributor
Ford-Werke GmbH	Ford Motor Company Ltd.
Edsel-Ford-Str. 2-14	Parts Distribution Centre
50769 Cologne	Royal Oak Way South
Germany	NN11 8NT Daventry, Northants
+49 221 90-33333	United Kingdom
sdseu@ford.com	+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

2. SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Health hazards	Respiratory sensitisation, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
----------------	---------------------------------------	------	--

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard pictograms



Signal word

Danger

Contains

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate; 4,4'-methylenediphenyl diisocyanate; 4,4'-methylenediphenyl diisocyanate, oligomers

Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

Prevention

P261 Avoid breathing mist, vapours.

P284

[In case of inadequate ventilation] wear respiratory protection.

Response

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311

If experiencing respiratory symptoms: Call a doctor, a POISON CENTER.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

3. SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	1 - < 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	(Note C)
Alkanes, C9-12-iso-	90622-57-4 292-459-0	1 - < 2	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413	
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate	905-806-4 01-2119457015-45-XXXX	0.1 - < 1	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335 (C >= 5) Eye Irrit. 2, H319 (Note C)(Note 2)
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47-XXXX	0.1 - < 0.5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335 (Note C)(Note 2)

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
4,4'-methylenediphenyl diisocyanate, oligomers	25686-28-6 500-040-3 01-2119457013-49-XXXX	0.1 - < 0.2	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) Skin Irrit. 2, H315 (C >= 5) Eye Irrit. 2, H319 (C >= 5) STOT SE 3, H335 (Note 2)(Note C)

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

4. SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Call a poison center or a doctor if you feel unwell.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

Skin contact

Wash skin with plenty of water.

Eyes contact

Rinse eyes with water as a precaution.

Ingestion

Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media

dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions

Use water spray or fog for cooling exposed containers. In case of fire: stop leak if safe to do so.

Protection during firefighting

Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

6. SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures Ventilate spillage area. Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Protective equipment Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment Stop leak without risks if possible.

Methods for cleaning up Mechanically recover the product.

Other information Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections For further information refer to section 13.

7. SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Keep away from ignition sources. Store in a well-ventilated place. Keep container tightly closed.

Storage temperature 15 - 25 °C

7.3. Specific end use(s) No additional information available.

8. SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EU

Regulation	Substance	Type	Value
COMMISSION DIRECTIVE 2000/39/EC	Xylene (1330-20-7) Xylene, mixed isomers, pure	IOELV TWA	221 mg/m ³
		IOELV TWA	50 ppm
		IOELV STEL	442 mg/m ³
		IOELV STEL	100 ppm
		Notes	Skin

United Kingdom

Regulation	Substance	Type	Value
EH40. HSE	Xylene (1330-20-7) Xylene	WEL TWA	220 mg/m ³ o-,m-,p- or mixed isomers
		WEL TWA	50 ppm o-,m-,p- or mixed isomers
		WEL STEL	441 mg/m ³ o-,m-,p- or mixed isomers
		WEL STEL	100 ppm o-,m-,p- or mixed isomers
		Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological

United Kingdom

monitoring guidance values are listed in Table 2)

DNEL: Derived no effect level

Components	Type	Route	Value	Form
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate	Worker	Inhalation	0.1 mg/m ³	Acute - local effects
		Inhalation	0.05 mg/m ³	Long-term - local effects
	Consumer	Inhalation	0.05 mg/m ³	Acute - local effects
		Inhalation	0.025 mg/m ³	Long-term - local effects
4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	Inhalation	0.1 mg/m ³	Acute - local effects
		Inhalation	0.05 mg/m ³	Long-term - local effects
	Consumer	Inhalation	0.05 mg/m ³	Acute - local effects
		Inhalation	0.025 mg/m ³	Long-term - local effects
4,4'-methylenediphenyl diisocyanate, oligomers (25686-28-6)	Worker	Inhalation	0.1 mg/m ³	Acute - local effects
		Inhalation	0.05 mg/m ³	Long-term - local effects
	Consumer	Inhalation	0.05 mg/m ³	Acute - local effects
		Inhalation	0.025 mg/m ³	Long-term - local effects
Xylene (1330-20-7)	Worker	Inhalation	289 mg/m ³	Acute - systemic effects
		Dermal	180 mg/kg bodyweight/day	Long-term - systemic effects
		Inhalation	77 mg/m ³	Long-term - systemic effects
	Consumer	Inhalation	289 mg/m ³	Long-term - local effects
		Inhalation	174 mg/m ³	Acute - systemic effects
		Inhalation	174 mg/m ³	Acute - local effects
		Oral	1.6 mg/kg bodyweight/day	Long-term - systemic effects
		Inhalation	14.8 mg/m ³	Long-term - systemic effects
Dermal	108 mg/kg bodyweight/day	Long-term - systemic effects		

PNEC: Predicted no effect concentration

Components	Type	Route	Value	Form
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate	Not applicable	Freshwater	1 mg/l	Intermittent release
		Seawater	0.1 mg/l	
		Freshwater	10 mg/l	
		Soil	1 mg/kg dwt	
		STP	1 mg/l	
4,4'-methylenediphenyl diisocyanate (101-68-8)	Not applicable	Freshwater	1 mg/l	Intermittent release
		Seawater	0.1 mg/l	
		Freshwater	10 mg/l	
		Soil	1 mg/kg dwt	
		STP	1 mg/l	
4,4'-methylenediphenyl diisocyanate, oligomers (25686-28-6)	Not applicable	Freshwater	1 mg/l	Intermittent release
		Seawater	0.1 mg/l	
		Freshwater	10 mg/l	
		Soil	1 mg/kg dwt	
		STP	1 mg/l	
Xylene (1330-20-7)	Not applicable	Freshwater	0.327 mg/l	

Seawater	0.327 mg/l	
Freshwater	0.327 mg/l	Intermittent release
sediment	12.46 mg/kg dwt	Freshwater
sediment	12.46 mg/kg dwt	Seawater
Soil	2.31 mg/kg dwt	
STP	6.58 mg/l	

8.2. Exposure controls

Appropriate engineering controls Ensure good ventilation of the work station

Materials for protective clothing No additional information available.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection Chemical goggles or safety glasses

Skin protection

Hand protection

The protective gloves to be used must comply with the specification of EU directive 89/686/EC and the resultant standard EN374. The above given information is based on laboratory test in line with EN374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove.

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0.4 mm	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0.4 mm	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
Other protective measures		No additional information available.	
Respiratory protection		Wear respiratory protection	
Device	Filter type	Condition	Comments
Full face mask	Filter P (white)	Dust protection	EN 14387
Thermal hazard protection		No additional information available.	
Environmental exposure controls		Avoid release to the environment.	

9. SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste.
Colour	white.
Odour	solvents-like.
Odour threshold	No data available.
pH	No data available.
Relative evaporation rate (butylacetate=1)	No data available.
Melting point	No data available.
Freezing point	Not applicable
Boiling point	No data available.
Flash point	Not applicable
Auto-ignition temperature	> 200 °C
Decomposition temperature	No data available.
Flammability (solid, gas)	Non flammable
Vapour pressure	< 100 hPa @ 20°C
Relative vapour density at 20 °C	No data available.
Relative density	Not applicable
Density	1.19 g/cm ³ @ 20°C
Solubility	insoluble in water.

Log Pow	No data available.
Viscosity, kinematic	Not applicable
Viscosity, dynamic	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.
Explosive limits	Not applicable
Lower explosive limit (LEL)	0.1 vol %
Upper explosive limit (UEL)	7.6 vol %

9.2. Other information

VOC (EU)	5.9 %
----------	-------

10. SECTION 10: Stability and reactivity

10.1. Reactivity	Reacts with water. Possible pressure build-up.
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
10.4. Conditions to avoid	humidity.
10.5. Incompatible materials	alcohols. Amines. Water.
10.6. Hazardous decomposition products	Nitrogen oxides. Hydrogen chloride. Sulphur oxides. On exposure to high temperature, may decompose, releasing : Isocyanates. On contact with humidity, releases: Carbon dioxide.

11. SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Not classified
----------------	----------------

Mixture

Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
Clinched Flange Sealer		ATE	Dermal	> 5000	mg/kg		(calculated value)
		ATE	Inhalation	> 5	mg/l/4h		(calculated value)

Substance

Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
Xylene (1330-20-7)		LD50	Dermal	> 1700	mg/kg	rabbit	
		LC50	Inhalation	11	mg/l/4h	rat	

Skin corrosion/irritation	Based on available data, the classification criteria are not met
Serious eye damage/irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

12. SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

Xylene (1330-20-7)

Persistence and degradability Readily biodegradable, according to appropriate OECD test.

Biodegradation > 60 % (OECD 301A-F method)

12.3. Bioaccumulative potential

Xylene (1330-20-7)

Bioconcentration factor (BCF REACH) 8.5 7days; Oncorhynchus mykiss (Rainbow trout)

Log Pow 3.12

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

Clinched Flange Sealer

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available.

13. SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Dispose of contents/container in accordance with licensed collector's sorting instructions.

European List of Waste (LoW) code

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 06 mixed packaging

14. SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) Not applicable

UN-No. (IMDG) Not applicable

UN-No. (IATA) Not applicable

UN-No. (ADN) Not applicable

UN-No. (RID) Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) Not applicable

Proper Shipping Name (IMDG) Not applicable

Proper Shipping Name (IATA) Not applicable

Proper Shipping Name (ADN) Not applicable

Proper Shipping Name (RID) Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) Not applicable

IMDG

Transport hazard class(es) (IMDG) Not applicable

IATA

Transport hazard class(es) (IATA) Not applicable

ADN

Transport hazard class(es) (ADN) Not applicable

RID

Transport hazard class(es) (RID) Not applicable

14.4. Packing group

Packing group (ADR) Not applicable

Packing group (IMDG) Not applicable

Packing group (IATA) Not applicable

Packing group (ADN) Not applicable

Packing group (RID) Not applicable

14.5. Environmental hazards

Dangerous for the environment No

Marine pollutant No

Other information No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

15. SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006

Xylene	3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008
Alkanes, C9-12-iso- - Xylene	3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
Alkanes, C9-12-iso- - Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate - 4,4'-methylenediphenyl diisocyanate, oligomers - Xylene	3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
Alkanes, C9-12-iso-	3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
Xylene	40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
4,4'-methylenediphenyl diisocyanate	56(a) Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
4,4'-methylenediphenyl diisocyanate	56. Methylenediphenyl diisocyanate (MDI)
Contains no substance on the REACH candidate list	
Contains no REACH Annex XIV substances	

VOC (EU) 5.9 %

National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

16. SECTION 16: Other information

Abbreviations and acronyms

	REACH-no.
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE	Acute Toxicity Estimate.
BCF	Bioconcentration factor.
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
DMEL	Derived Minimal Effect level.
DNEL	Derived-No Effect Level.
EC50	Median effective concentration.
IARC	International Agency for Research on Cancer.
IATA	International Air Transport Association.
IMDG	International Maritime Dangerous Goods.
LC50	Median lethal concentration.
LD50	Median lethal dose.
LOAEL	Lowest Observed Adverse Effect Level.

NOAEC	No-Observed Adverse Effect Concentration.
NOAEL	No-Observed Adverse Effect Level.
NOEC	No-Observed Effect Concentration.
OECD	Organisation for Economic Co-operation and Development.
PBT	Persistent Bioaccumulative Toxic.
PNEC	Predicted No-Effect Concentration.
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail.
RRN	REACH Registration Number.
SDS	Safety Data Sheet.
STP	Sewage treatment plant.
TLM	Median Tolerance Limit.
vPvB	Very Persistent and Very Bioaccumulative.

Full text of H- and EUH-statements

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4.
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4.
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4.
Asp. Tox. 1	Aspiration hazard, Category 1.
Carc. 2	Carcinogenicity, Category 2.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2.
Flam. Liq. 3	Flammable liquids, Category 3.
Resp. Sens. 1	Respiratory sensitisation, Category 1.
Skin Irrit. 2	Skin corrosion/irritation, Category 2.
Skin Sens. 1	Skin sensitisation, Category 1.
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2.
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Resp. Sens. 1	H334	Calculation method
---------------	------	--------------------

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name: Clinched Flange Sealer
Ford Int. Ref. No.: 102972

Page: 1/1
Print Date: 13.03.2017

Involved Products:

	Finiscode	Part number	Container Size:
1.	1 790 195	1S5J M4G245 AB	310 ml