REAR AXLE OIL SAE 90

SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	Rear Axle Oil SAE 90
Product code	:	Ford Internal Ref.: 108289
SDS Number	:	5187
Product use	:	Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

1.2.2. Uses advised against

Function or use category

: Transmission, Axle and Power Steering Fluids

Restrictions on use

: None known

1.3. Details of the supplier of the safety data sheet

Supplier	Distributor
Ford-Werke GmbH	Ford Motor Company Ltd.
Edsel-Ford-Str. 2-14	Parts Distribution Centre
50769 Cologne	Royal Oak Way South
Germany	NN11 8NT Daventry, Northants
+49 221 90-33333	United Kingdom
sdseu@ford.com	+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Environmental hazards Hazardous to the aquatic environment – H411		Toxic to aquatic life with long lasting effects.	
	Chronic Hazard, Category 2		

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms

Signal word

Hazard statements





ISSUE DATE: 23.09.2014 REVISION DATE: 24.07.2023 SUPERSEDES: 24.09.2020 VERSION: 5.0

H411	Toxic to aquatic life with long lasting effects.	
Precautionary statements		
Prevention		
P273	Avoid release to the environment.	

Collect spillage.

P391 **EUH-statements**

Response

EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14- alkyl (branched)	- 931-384-6 - 01-2119493620-38-XXXX	1 - < 2,5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	(9.39 ≤ C < 100) Skin Sens. 1, H317 (50 < C ≤ 100) Eye Irrit. 2, H319 UVCB
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)- alkylamines	1213789-63-9 627-034-4 - 01-2119473797-19-XXXX	0,1 -< 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	UVCB

Comments

UVCB: Substances of Unknown or Variable composition, Complex reaction products or Biological · materials

Full text of H- and FUH-statements; see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

M: M-Factor

: Ensure that medical personnel are aware of the material(s) involved, and take precautions to

: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if

: Wash skin with plenty of water and soap. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

you feel unwell.

protect themselves. Discard contaminated clothing.

First-aid measures after eye contact	: Consult an ophtalmologist if irritation persists. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum).
First-aid measures after ingestion	: Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effects, bot	h acute and delayed
Symptoms/effects after skin contact Symptoms/effects after eye contact	May cause an allergic skin reaction. May cause skin irritation.May cause eye irritation.
4.3. Indication of any immediate medical attent Treat symptomatically.	ion and special treatment needed
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	 carbon dioxide (CO2), powder, water spray. For large fire: Alcohol-resistant foam. Do not use a water jet since it may cause the fire to spread.
5.2. Special hazards arising from the substanc	e or mixture
Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO2).
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: stop leak if safe to do so. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Prevent runoff from entering water courses, sewers and basements.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equipment	nt and emergency procedures
General measures	: Do not touch or walk on the spilled product. If spilled, may cause the floor to be slippery.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin, eyes and clothing. Avoid breathing dust, mist or spray. Do not attempt to take action without suitable protective equipment. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Local authorities should be advised if significant spillages cannot be contained.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Keep unnecessary personnel away.
6.2. Environmental precautions	

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible. Move containers from fire area if it can be done without personal risk.
Methods for cleaning up	: Small spills: Clean surface thoroughly to remove residual contamination. Wipe up with absorbent material (e.g. cloth, fleece). Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Never return spills in original containers for re-use.
Other information	: The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas. Dispose in accordance with all applicable regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13:" Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Prevent aerosol formation or splashes. Do not empty into drains. Do not get in eyes, on skin, or on
	clothing. Do not breathe vapour/aerosol.
Hygiene measures	: Always observe good personal hygiene measures, such as washing after handling the material and
	before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to
	remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed. Keep out of reach of children. Store in a well-ventilated place. Keep cool. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible products	: Strong acids. Strong bases. Strong oxidizing agent.
Incompatible materials	: Heat sources.
7.3. Specific end use(s)	

Transmission, Axle and Power Steering Fluids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (-)

DNEL/DMEL (Workers)	
Acute - local effects, dermal	160 µg/cm²
Long-term - systemic effects, dermal	12.5 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm²
Long-term - systemic effects, inhalation	4.28 mg/m ³
DNEL/DMEL (General population)	
Acute - local effects, dermal	160 µg/cm ²
Long-term - systemic effects,oral	0.25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.09 mg/m³
Long-term - systemic effects, dermal	6.25 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm²
PNEC (Water)	
PNEC aqua (freshwater)	2.4 µg/L
PNEC aqua (marine water)	0.24 µg/L
PNEC aqua (intermittent, freshwater)	150 µg/L
PNEC aqua (intermittent, marine water)	15 µg/L

PNEC (Sediment)	
PNEC sediment (freshwater)	12.9 µg/kg dw
PNEC sediment (marine water)	1.29 µg/kg dw
PNEC (Soil)	
PNEC soil	1.17 µg/kg dw
PNEC (Oral)	
PNEC oral (secondary poisoning)	10 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	24.33 mg/l
(Z)-octadec-9-enylamine, C16-18-(even numbered, satu	rated and unsaturated)-alkylamines (1213789-63-9)
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	1 mg/m³
Long-term - systemic effects, inhalation	0.38 µg/m³
Long-term - local effects, inhalation	1 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	40 µg/kg bw/day
Long-term - systemic effects, inhalation	0.035 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.26 µg/L
PNEC aqua (marine water)	0.026 µg/L
PNEC aqua (intermittent, freshwater)	1.6 µg/L
PNEC (Sediment)	
PNEC sediment (freshwater)	3.76 mg/kg dwt
PNEC sediment (marine water)	0.376 mg/kg dwt
PNEC (Soil)	
PNEC soil	10 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	550 μg/L
8.1.5. Control banding	

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

EN 166. Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection:

Long sleeved protective clothing

Hand protection:

Protective gloves. ISO 374-1. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment **8.2.2.3. Respiratory protection**

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Dhusiaal stata	· Liquid
Physical state	: Liquid
Colour	: dark brown.
Appearance	: Liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 220 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: 184 mm²/s @ 40°C
Solubility	: insoluble in water.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0.91 g/cm³ @ 15°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available

Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content	:	0.32 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong alkalis. Strong acids. Strong oxidizers.

10.6. Hazardous decomposition products

During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Based on available data, the classification criteria are not met
Acute toxicity (dermal)	:	Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	:	Based on available data, the classification criteria are not met

Rear Axle Oil SAE 90

	ATE CLP (oral)	> 5000 mg/kg
--	----------------	--------------

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (-)		
LD50 oral 2000 mg/kg bodyweight (OECD 401 method)		
(Z)-octadec-9-enylamine, C16-18-(even nu	mbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
LD50 oral rat	1689 mg/kg bodyweight	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met	
Serious eye damage/irritation	: Based on available data, the classification criteria are not met	
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not metNo classification due to test data	
Germ cell mutagenicity	: Based on available data, the classification criteria are not met	
Carcinogenicity	: Based on available data, the classification criteria are not metAll hydrocarbons in this mixture: Note L is applicable (DMSO <3%), therefore no classification as carcinogen	
Reproductive toxicity	: Based on available data, the classification criteria are not met	
STOT-single exposure	: Based on available data, the classification criteria are not met	

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
STOT-single exposure May cause respiratory irritation.		
STOT-repeated exposure :	Based on available data, the classification criteria are not met	
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard :	Based on available data, the classification criteria are not met	
Rear Axle Oil SAE 90		
Viscosity, kinematic	184 mm²/s @ 40°C	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

-	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term	: Based on available data, the classification criteria are not met
(acute)	
Hazardous to the aquatic environment, long-term	: Toxic to aquatic life with long lasting effects.
(chronic)	

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (-)

LC50 - Fish [1]	24 mg/l (OECD 203 method)		
EC50 - Crustacea [1]	91.4 mg/l (OECD 202 method)		
EC50 96h - Algae [1]	15 mg/l (OECD 201 method)		
NOEC chronic crustacea	0.12 mg/l ; 21 d; (OECD 211 method)		
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)			
LC50 - Fish [1]	0.06 mg/l (OECD 203 method)		

EC50 - Crustacea [1]	0.011 mg/l (OECD 202 method)
NOEC chronic crustacea	0.013 mg/l ; 21 d, (OECD 211 method)

12.2. Persistence and degradability

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

(-) Biodegradation

3.6 % (28 d, ASTM D-5864-95)

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Rear Axle Oil SAE 90

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Sewage disposal recommendations Product/Packaging disposal recommendations

Additional information Ecology - waste materials European List of Waste (LoW) code : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

:	Collect and reclaim or dispose in closed containers at licensed waste disposal site. Empty
	containers or liners may retain some product residues. This material and its container must be
	disposed of in a safe manner (see: Disposal instructions).
:	Do not pierce or burn, even after use.

: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

- : Dispose in accordance with all applicable regulations.
- : Avoid discharge into drains, water courses or onto the ground.
- : The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
 - 13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils
 - 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	: UN 3082
UN-No. (IMDG)	: UN 3082
UN-No. (IATA)	: UN 3082
UN-No. (ADN)	: UN 3082
UN-No. (RID)	: UN 3082
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12- 14-alkyl (branched); (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (IMDG)	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12- 14-alkyl (branched); (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s. (Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)- alkylamines)
Proper Shipping Name (ADN)	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12- 14-alkyl (branched); (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (RID)	 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12- 14-alkyl (branched); (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: 9
Danger labels (ADR)	: 9
IMDG	
Transport hazard class(es) (IMDG)	: 9
Product codo: Ford Internal Pof : 108280	

Product code: Ford Internal Ref.: 108289

Danger labels (IMDG)	: 9
ΙΑΤΑ	
Transport hazard class(es) (IATA)	: 9
Hazard labels (IATA)	: 9
ADN	
Transport hazard class(es) (ADN)	: 9
Danger labels (ADN)	: 9
RID	
Transport hazard class(es) (RID)	: 9
Danger labels (RID)	: 9
14.4. Packing group	
Packing group (ADR)	: 111
Packing group (IMDG)	: 111
Packing group (IATA)	: 111
Packing group (ADN)	: 111
Packing group (RID)	: 111
14.5. Environmental hazards	
Dangerous for the environment	: Yes
Marine pollutant	: Yes
Other information	: No supplementary information available.
14.6. Special precautions for user	
Overland transport	
Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 51
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Hazard identification number (Kemler No.)	: 90
Tunnel restriction code (ADR) EAC code	: - : •3Z
	. •32

Transport by sea

Special provisions (IMDG)	:	274, 335, 969
Limited quantities (IMDG)	:	5 L
Packing instructions (IMDG)	:	LP01, P001
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-F
Stowage category (IMDG)	:	А

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L
Inland waterway transport	
Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5L
Carriage permitted (ADN)	: T

Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Packing instructions (RID)	: P001, IBC03, LP01, R001
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on		
3(b)	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-		
	14-alkyl (branched); (Z)-oct	adec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	
3(c)	Rear Axle Oil SAE 90 ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene		
	oxide and amines, C12-14-al	lkyl (branched) ; (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-	
	alkylamines		
Contains no substance(s) list	ted on the REACH Candidate I	List	
Contains no substance(s) list	ted on REACH Annex XIV (Aut	thorisation List)	
Contains no substance(s) list	ted on the PIC list (Regulation	EU 649/2012 concerning the export and import of hazardous chemicals)	
Contains no substance(s) list	ted on the POP list (Regulation	n EU 2019/1021 on persistent organic pollutants)	
VOC content	:	0.32 %	
Other information, restriction	and prohibition regulations :	Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.	
Directive 2012/18/EU (SEVE	ESO III)		
Seveso Additional informatio	n :	Not applicable	

	Lower-tier	Upper-tier
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Label elements. Regulatory information. Composition/information on ingredients.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE BCF	Acute Toxicity Estimate Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived Minima Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IANU	

Qualifying quantity (tonnes)

ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50		
LOAEL	Median lethal dose Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD		
PBT	Organisation for Economic Co-operation and Development Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH		
SDS	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
	Safety Data Sheet	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
STP	Sewage treatment plant	
TLM	Median Tolerance Limit	
vPvB	Very Persistent and Very Bioaccumulative	
SDS	Safety Data Sheet	
OEL	Occupational Exposure Limit	
RRN	REACH Registration no.	
CAO	Cargo Aircraft Only	
PCA	Passenger and Cargo Aircraft	
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures,	
	amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.	
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.	
Full text of H- and EUH-sta	atements	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and	
2011200	amines, C12-14-alkyl (branched). May produce an allergic reaction.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H400 H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
11711		
Skin Corr 1B		
Skin Corr. 1B Skin Sens, 1	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Sens. 1	Skin corrosion/irritation, Category 1, Sub-Category 1B Skin sensitisation, Category 1	
Skin Sens. 1 STOT RE 2	Skin corrosion/irritation, Category 1, Sub-Category 1B Skin sensitisation, Category 1 Specific target organ toxicity – Repeated exposure, Category 2	
Skin Sens. 1	Skin corrosion/irritation, Category 1, Sub-Category 1B Skin sensitisation, Category 1	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Aquatic Chronic 2 H411 Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name: Rear Axle Oil SAE 90

Ford Int. Ref. No.: 108289

Revision Date: 24.07.2023

Involved Products:

Finiscode	Part number
1 1 781 300	2L5J M2C9102 AB

Container Size: 1 I