# SAFETY DATA SHEET



according to regulation (EU) No 2015/830

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Silicone Sealant LG

of the mixture

Registration number

**Synonyms** None. SDS number 8051

**Product code** Ford Internal Ref.: 135024

Issue date 23-October-2014

Version number 3.0

**Revision date** 20-April-2016 Supersedes date 23-October-2014 **Product use** Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Sealers and Adhesives **Identified uses** 

None known. Uses advised against

1.3. Details of the supplier of the safety data sheet

Company name Ford Motor Company Ltd. Parts Distribution Centre **Address** Royal Oak Way South

NN11 8NT Daventry, Northants

United Kingdom

Telephone number +44 1327 305 198 Ford-Werke GmbH **Address** Edsel-Ford-Str. 2-14

50769 Köln

Germany

Telephone number +49 221 90-33333 E-mail sdseu@ford.com

1.4 Emergency telephone

number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

Serious eye damage/eye irritation Category 1 H318 - Causes serious eye

damage.

Skin sensitisation H317 - May cause an allergic skin Category 1

reaction.

Carcinogenicity Category 2 H351 - Suspected of causing

cancer.

## 2.2. Label elements

# Label according to Regulation (EC) No. 1272/2008 as amended

Butan-2-one O,O',O",O"-silanetetrayltetraoxime, Butanone oxime, Silicon Compounds Contains:

Hazard pictograms

Material name: Silicone Sealant LG



Signal word Danger

**Hazard statements** 

May cause an allergic skin reaction. H317 Causes serious eve damage. H318 Suspected of causing cancer. H351

Precautionary statements

Prevention

Obtain special instructions before use. P201

Wear protective gloves/protective clothing/eye protection/face protection. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing

Immediately call a POISON CENTER/doctor. P310

Storage None. Disposal None. Supplemental label information None.

2.3. Other hazards The mixture contains no substance that fulfils the criteria of a PBT- or vPvB substance.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**General information** 

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Silicon Compounds		5 - < 10	N/A	-	-	
Classification:	Skin Sens.	. 1;H317, Eye	Dam. 1;H318, ST	OT RE 2;H373		
Butanone oxime		1 - < 5	96-29-7 202-496-6	-	616-014-00-0	
Classification:	Flam. Liq. 2;H351	3;H226, Acut	e Tox. 4;H312, Sk	in Sens. 1;H317, Eye Dam. 1;F	l318, Carc.	
Butan-2-one		0.1 - < 1	34206-40-1	01-2119982966-14-XXXX	-	

O,O',O",O"-silanetetrayltetraoxime 251-882-0

Classification: Flam. Sol. 1;H228, Skin Sens. 1;H317, Eye Irrit. 2;H319, STOT RE 2;H373

The full text for all H-statements is displayed in section 16. Composition comments

# **SECTION 4: First aid measures**

**General information** IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware

of the material(s) involved, and take precautions to protect themselves. Wash contaminated

clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin

reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). media

Material name: Silicone Sealant LG SDS UK Ford Internal Ref.: 135024 Version #: 3.0 Revision date: 20-April-2016 Issue date: 23-October-2014

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled

containers.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

# **SECTION 7: Handling and storage**

7.1. Precautions for safe

handling

Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not get this material in contact with eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any

Do not allow contact with water.

incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials

(see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

**Biological limit values** 

No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.

**Recommended monitoring** procedures

Derived no-effect level (DNEL)

Components	Туре	Route	Value	Form
Butan-2-one O,O',O",O"-silanete 34206-40-1)	Consumer etrayltetraoxime (CAS	Dermal	0.067 mg/kg/BW/day	
Comments:	Long term exposure systemic effects			
		Inhalation	0.232 mg/m3	
Comments:	Long term exposure systemic effects			
		Oral	0.067 mg/kg/BW/day	
Comments:	Long term exposure systemic effects			

Material name: Silicone Sealant LG Ford Internal Ref.: 135024 Version #: 3.0 Revision date: 20-April-2016 Issue date: 23-October-2014 
 Components
 Type
 Route
 Value
 Form

 Professional
 Dermal
 0.134 mg/kg/BW/day

 Comments:
 Long term exposure systemic effects

 Inhalation
 0.942 mg/m3

 Comments:
 Long term exposure systemic effects

Predicted no effect concentrations (PNECs)

Components		Туре	Route	Value	Form
Butan-2-one O,O',O",O"-silanetetrayltetraoxime (CAS 34206-40-1)		Not applicable F	Freshwater	0.017 mg/l	
			Oral	2.97 mg/kg	
Comments:	food, predators				
			Seawater	0.002 mg/l	
			Sediment	9835.346 mg/kg	
Comments:	Freshwater				
			Sediment	983.535 mg/kg	
Comments:	Seawater				
			Soil	1157.93 mg/kg	
			STP	4.825 mg/l	

# 8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

### Individual protection measures, such as personal protective equipment

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

- Hand protection Nitrile.

Glove thickness 0.4 mm. Break through time >= 480 min

Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Hand protection in case of splash contact

Nitrile.

Glove thickness 0.4 mm. Break through time >= 480 min

Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

The protective gloves to be used must comply with the specification of EU directive 89/686/EC and the resultant standard EN374. The above given information is based on laboratory test in line with EN374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove.

can reduce the protective effect provided by the recommended glove.

- Other Wear appropriate chemical resistant clothing

Respiratory protection Thermal hazards In case of insufficient ventilation, wear suitable respiratory equipment.

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Observe any medical surveillance requirements. Always observe good personal hygiene

measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

**Environmental exposure** 

Material name: Silicone Sealant LG

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state
Form
Colour
Grey.
Odour
Odour threshold
Ph
Not available.
Melting point/freezing point
Not available.

Initial boiling point and boiling

> 200 °C (> 392 °F)

range

Flash point > 93.0 °C (> 199.4 °F)

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapour pressure < 5 mm Hg @ 50°C

< 700 mbar @ 50°C

Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Polymerises under humid conditions

Solubility (other) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available.

Not available.

Not available.

Not available.

Not explosive.

Oxidising properties 9.2. Other information

**Density** 1.50 g/cm<sup>3</sup> @20°C

VOC (EU) < 5 % VOC (CH) < 3 %

# **SECTION 10: Stability and reactivity**

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability**Material is stable under normal conditions.

Not oxidising.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Exposure to air. Moisture.10.5. Incompatible materials Strong oxidising agents.

**10.6. Hazardous decomposition products**Methylethylketoxime is formed during the curing process.

Methanol will be released slowly on contact with moisture.

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Material name: Silicone Sealant LG

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

**Eye contact** Causes serious eye damage.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred Symptoms

vision. Permanent eye damage including blindness could result. May cause an allergic skin

reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

**Acute toxicity** May cause an allergic skin reaction.

**Product Species Test results** 

Silicone Sealant LG

**Acute Dermal** 

> 2000 mg/kg (calcd. ATE)

Components **Species Test results** 

Butanone oxime (CAS 96-29-7)

**Acute Dermal** 

1100 mg/kg (acc. CLP 3.1.2)

Skin corrosion/irritation

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity Suspected of causing cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ

toxicity - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated

exposure

Based on available data, the classification criteria are not met.

No data is available on the degradability of this product.

Aspiration hazard

Mixture versus substance

Not likely, due to the form of the product.

information

No information available.

Other information Not available.

**SECTION 12: Ecological information** 

12.1. Toxicity

The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and degradability

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol

/water (log Kow)

Not available.

**Bioconcentration factor (BCF)** Not available. 12.4. Mobility in soil

No data available.

12.5. Results of PBT

and vPvB assessment The mixture contains no substance that fulfils the criteria of a PBT- or vPvB substance.

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**SECTION 13: Disposal considerations** 

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: Silicone Sealant LG

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

08 04 09 15 01 10

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

#### **ADR**

Not regulated as dangerous goods.

#### **IATA**

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulations

Not applicable.

#### Restrictions on use

# Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Butanone oxime (CAS 96-29-7)

Other regulations

Pregnant women should not work with the product, if there is the least risk of exposure. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

# Other EU regulations

# Directive 94/33/EC on the protection of young people at work, as amended

Butanone oxime (CAS 96-29-7) Silicon Compounds (CAS N/A)

# Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended

Butanone oxime (CAS 96-29-7) **VOC (EU):** < 5 %

## Directive 2012/18/EU on major accident hazards involving dangerous substances

Not applicable

**National regulations** 

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

## 15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

Material name: Silicone Sealant LG

#### List of abbreviations

AC: Article category.

acc., acc.to: according, according to.

ACGIH: American Conference of Governmental Industrial Hygienists.

AFNOR: French Institute for Standards (Association Française de Normalisation).

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures).

ADR: European agreement concerning the international carriage of dangerous goods by road

(Accord européen relatif transport des merchandises dangereuses par route). AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

AICS: Australian Inventory of Chemical Substances. ANSI: American National Standards Institute. AOEL: Acceptable Operator Exposure Level.

AOX: adsorbable organic halogen compounds.

approx.: approximately. ASTM: ASTM International.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

BAM: Federal Institute for Materials Research and Testing, Germany (Bundesanstalt für Materialforschung und -prüfung).

Maximum permissible concentration of biological working substances (BAT: Biologische Arbeitsstofftoleranzwerte).

BAuA: Federal Institute for Occupational Health and Safety, Germany (Bundesanstalt für Arbeitsschutz und Arbeitsmedizin).

BCF: Bio-concentration factor.

BET: Brunauer-Emmett-Teller.

BLV: Biological Limit Value.

BLV: Biological Limit Value (BGW: Biologischer Grenzwert, Austria).

BMGV: Biological Monitoring Guidance Value (EH40,UK).

BSI: British Standards Institution.

BS: British Standard.

BOD5: Biochemical oxygen demand within 5 days.

BOD: Biochemical oxygen demand.

bw: Body weight. calcd.: calculated.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization (Comité Européen de Normalisation).

CESIO: European Committee on Organic Surfactants and their Intermediates (Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques).

ChemRRV: Ordinance on the risk reduction related to chemical products (ChemRRV:

Chemikalien-Risikoreduktions-verordnung, Switzerland).

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction.

CNS: Central Nervous System.

CNT: Carbon nanotubes.

COD: Chemical Oxygen Demand.

CSA: Chemical Safety Assessment.

CSR: Chemical Safety Report.

DETEC: Swiss Federal Department of the Environment, Transport, Energy and Communications.

DIN: German Standards Institute / German industrial norm (Deutsches Institut für Normung / Deutsche Industrienorm).

DMEL: Derived Minimum Effect Level.

DNEL: Derived No Effect Level.

DOC: Dissolved organic carbon.

DPD: Directive 1999-45-EC / Dangerous Preparations Directive.

DSD: Directive 67/548-EC / Dangerous Substances Directive.

DSL: Canada, Domestic Substances List.

DU: Downstream User.

dw: dry weight.

e.g.: For example, for instance.

EBW: Exposure Based Waiving.

EC: European Community.

EC50: Effective Concentration 50%.

ECHA: European Chemical Agency.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

EN: European norm.

ENCS: Japan, Inventory of Existing and New Chemical Substances.

EPA: United States Environmental Protection Agency.

ERC: Environmental release category.

ES: Exposure scenario.

EU: European Union

EUSES: European Union System for the Evaluation of Substances.

EWC/EWL: European Waste Catalogue.

GCL: General concentration limit.

gen.: general.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

GLP: Good Laboratory Practice.

GW/VL: Occupational exposure limit value.

GW-kw: Occupational exposure limit value - short term.

GW-M/VL-M: Occupational exposure limit value - "Ceiling".

GWP: Global Warming Potential.

HPV: High Production Volume Chemicals. HEPA: High Efficiency Particulate Air.

IARC: International Agency for Research on Cancer.

Material name: Silicone Sealant LG

IATA: International Air Transport Association.

IBC: Intermediate Bulk Container.

IBC Code: International Bulk Chemical (Code) (International Code for the Construction and

Equipment of Ships carrying Dangerous Chemicals in Bulk).

ICAO: International Civil Aviation Organization.

IC50: Inhibition Concentration 50%.

IECSC: Inventory of Existing Chemical Substances in China. IMDG Code: International Maritime Dangerous Goods Code.

IMO: International Maritime Organization.

incl.: including, inclusive.

ISO: International Standards Organization.

IUCLID: International Uniform Chemical Information Database.

IUPAC: International Union for Pure Applied Chemistry.

KECI: Korea Existing Chemicals Inventory.

LCA: Life Cycle Assessment.

LC: Lethal Concentration.

LC50: Lethal Concentration 50%.

LCLo: Lowest published lethal concentration.

LD50: Lethal Dose 50%.

LEV: Local exhaust ventilation.

LOAEL: Lowest observed adverse effect level.

LOEC: Lowest observable effect concentration.

LOEL: Lowest observable effect level.

LPV: Low Production Volume Chemicals.

LQ: Limited Quantities.

Air Quality Control Regulation (LRV: Luftreinhalteverordnung, Switzerland).

TLV-STEL: Threshold limit value - Short-term exposure limit / Technical reference concentration - short-time value (TRK-Kzw = Technische Richtkonzentration - Kurzzeitwert).

Maximum allowable workplace concentration – instantaneous value (MAK-Mow: Maximale Arbeitsplatzkonzentration – Momentanwert, Austria)

Maximum allowable workplace concentration – daily mean value / Technical standard concentration – daily mean value (MAK-Tmw, TRK-Tmw : Maximale Arbeitsplatzkonzentration -

Tagesmittelwert / TRK-Tmw = Technische Richtkonzentration – Tagesmittelwert, Austria).

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution From Ships.

MTD: Maximum tolerated dose.

MWCNT: Multi-walled carbon nanotubes.

n.a.: not applicable. N/A: Not available.

n.d.: not determined.

NLP: No Longer Polymers.

NDSL: Canada, Non-Domestic Substances List.

NF: French Norm (See AFNOR).

NFPA: National Fire Protection Association.

NIOSH: National Institute for Occupational Safety & Health.

NOAEC: No Observed Adverse Effect Concentration.

NOAEL: No observed adverse effect level.

NOEC: No observed effect concentration.

NOEL: No observed effect level.

NTP: National Toxicology Program.

NZIoC: New Zealand Inventory of Chemicals. ODP: Ozone Depletion Potential.

OECD: Organization for Economic Cooperation and Development.

OEL: Occupational Exposure Limit.

org.: organic.

OSHA: Occupational Safety & Health Administration.

PAH: Polycyclic Aromatic Hydrocarbons.

PBT: Persistent, bioaccumulative, toxic.

PC: Product category.

PE: Polyethylene.

PEC: Predicted Environmental Concentration.

PEL: Permissible Exposure Limit.

PIC: Prior Informed Consent.

PICCS: Philippines Inventory of Commercial Chemical Substances.

PNEC: Predicted No Effect Concentration.

POCP: Photochemical ozone creation potential (Photochemisches Ozonbildungspotenzial).

POP: Persistent Organic Pollutant.

PPORD: Product and Process Oriented Research and Development.

Material name: Silicone Sealant LG

SDS UK

PPE: Personal Protective Equipment.

PROC: Process category. RA: Risk Assessment.

RAR: Risk Assessment Report.

RCRA: Resource Conservation Recovery Act.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RMM: Risk Management Measure.

RTECS: Registry of Toxic Effects of Chemical Substances.

QSAR: Quantitative Structure Activity Relation.

SARA: Superfund Amendments and Reauthorization Act. SADT: Self-Accelerating Decomposition Temperature.

SCL: Specific concentration limit. SEA: socio economic analysis. STEL: Short-term Exposure Limit. STP: Sewage treatment plant.

SU: Sector of use.

SVHC: Substance of Very High Concern. SWCNT: single-walled carbon nanotubes.

ThOD: Theoretical oxygen demand.

TOC: Total Organic Carbon. TLV: Threshold Limit Value. TRA: Targeted Risk Assessment.

TRGS: Technical Rules for Hazardous Substances (German Standard)

TSCA: Toxic Substance Control Act. TWA: Time Weighted Average.

UC: Use category.

UDS: Use descriptor system. UEC: Use and exposure categories.

UN: United Nations.

UN RTDG: United Nations Recommendations on the Transport of Dangerous Goods.

UVCB: Unknown or Variable Composition, Complex Reaction Products, and Biological Materials. Regulation on combustible liquids (VbF: Verordnung über brennbare Flüssigkeiten, Austria).

Regulation of the Austria Minister for Labor and Social Affairs regarding health surveillance at the workplace (VGÜ = Verordnung des Bundesministers für Arbeit und Soziales über die

Gesundheitsüberwachung am Arbeitsplatz).

VOC: Volatile organic compounds.

vPvB: very Persistent, very Bioaccumulative.

WEL-TWA: Workplace Exposure Limit-Long term exposure limit (8-hour TWA(=time weighted average)reference period).

WEL-STEL: Workplace Exposure Limit-Short term exposure limit (15-minute reference period).

The classification for health and environmental hazards is derived by a combination of calculation

WoE: Weight of evidence.

WHMIS: Workplace Hazardous Materials Information System.

WHO: World Health Organization.

wwt: wet weight.

Information on evaluation method leading to the classification of mixture

References

Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapour.

methods and test data, if available.

H228 Flammable solid.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation. H351 Suspected of causing cancer.

 ${\sf H373}$  May cause damage to organs through prolonged or repeated exposure.

Revision information Training information

Material name: Silicone Sealant LG

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

# **Disclaimer**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Material name: Silicone Sealant LG
Ford Internal Ref.: 135024 Version #: 3.0 Revision date: 20-April-2016 Issue date: 23-October-2014

# **Attachment to the Safety Data Sheet**



Product Name:Silicone Sealant LGPage:1/1Ford Int. Ref. No.:135024Print Date: 20.04.2016

**Involved Products:** 

Finiscode Part number Container Size:

1. 1 842 621 YS4J M4G320 AB 50 ml