REPAIR ADHESIVE COMPONENT B



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 09.10.2014 REVISION DATE: 27.08.2025 SUPERSEDES: 13.09.2023

VERSION: 6.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Repair Adhesive Component B
Product code : Ford Internal Ref.: 135570

SDS Number : 7646

Unique Formula Identifier (UFI) : 69F3-2DK6-U005-T03M Product use : Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : adhesives

1.2.2. Uses advised against

Restrictions on use : Unknown

1.3. Details of the supplier of the safety data sheet

Supplier Distributor

Ford-Werke GmbH Ford Motor Company Ltd.

Edsel-Ford-Str. 2-14 Parts Distribution Centre
50769 Cologne Royal Oak Way South
Germany NN11 8NT Daventry, Northants

Repeated exposure, Category 2

+49 221 90-33333 United Kingdom sdseu@ford.com +44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

_			
Health hazards	Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
	Serious eye damage/eye irritation,	H319	Causes serious eye irritation.
	Category 2		
	Respiratory sensitisation, Category 1	H334	May cause allergy or asthma symptoms or
			breathing difficulties if inhaled.
	Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
	Carcinogenicity, Category 2	H351	Suspected of causing cancer.
	Specific target organ toxicity – Single	H335	May cause respiratory irritation.
	exposure, Category 3, Respiratory tract		
	irritation		
	Specific target organ toxicity –	H373	May cause damage to organs through

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

prolonged or repeated exposure.

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms





Signal word Danger

Contains Diphenylmethane diisocyanate, isomers and homologues; 4.4'-methylenediphenyl diisocyanate; o-

(p-isocyanatobenzyl)phenyl isocyanate; 2,2'-methylenediphenyl diisocyanate

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

P201 Obtain special instructions before use.
P261 Avoid breathing dust, mist, vapours.

P280 Wear eye protection, protective gloves, protective clothing.

Response

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER, doctor.

Extra phrases As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Diphenylmethane diisocyanate, isomers and homologues	9016-87-9 618-498-9	10 - < 15	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	$(0.1 \le C \le 100)$ Resp. Sens. 1; H334 $(5 \le C \le 100)$ Eye Irrit. 2; H319 $(5 \le C \le 100)$ Skin Irrit. 2; H315 $(5 \le C \le 100)$ STOT SE 3; H335
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0	10 - < 15	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h)	(0.1 ≤ C ≤ 100) Resp. Sens. 1; H334 (5 ≤ C ≤ 100) Eye Irrit. 2;

	615-005-00-9 01-2119457014-47-XXXX		Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	H319 $(5 \le C \le 100)$ Skin Irrit. 2; H315 $(5 \le C \le 100)$ STOT SE 3; H335 (Note C)(Note 2)
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1 227-534-9 615-005-00-9 01-2119480143-45-XXXX	1 - < 5	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	$(0.1 \le C \le 100)$ Resp. Sens. 1; H334 $(5 \le C \le 100)$ Eye Irrit. 2; H319 $(5 \le C \le 100)$ Skin Irrit. 2; H315 $(5 \le C \le 100)$ STOT SE 3; H335 (Note C)(Note 2)
2,2'-methylenediphenyl diisocyanate	2536-05-2 219-799-4 615-005-00-9 01-2119927323-43-XXXX	0.1 - < 1	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317	$(0.1 \le C \le 100)$ Resp. Sens. 1; H334 $(5 \le C \le 100)$ Eye Irrit. 2; H319 $(5 \le C \le 100)$ Skin Irrit. 2; H315 $(5 \le C \le 100)$ STOT SE 3; H335 (Note C)(Note 2)

Note 2 - The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you

feel unwell

First-aid measures after skin contact : Wash skin with plenty of water. Take off immediately all contaminated clothing and wash it before

reuse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately and

thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an

ophthalmologist if irritation persists.

First-aid measures after ingestion : Rinse mouth thoroughly. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: : Suspected of causing cancer. May cause damage to organs through prolonged or repeated

exposure.

Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if

inhaled. Shortness of breath.

Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction. Redness. Skin rash/inflammation.

Symptoms/effects after eye contact : Causes serious eye irritation. Conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry chemical, CO2, dry sand, or alcohol-resistant foam.

Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO2).

5.3. Advice for firefighters

Precautionary measures fire : Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Firefighting instructions : Use standard firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

anneative and full materials alething moved by come in case of fine

apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up. For further information refer to

section 8: "Exposure controls/personal protection".

Emergency procedures : Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Ventilate

spillage area. Wear appropriate protective equipment and clothing during clean-up. Local

authorities should be advised if significant spillages cannot be contained.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to

section 8: "Exposure controls/personal protection".

Emergency procedures : Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site. Never return spills in original containers

for re-use.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid release to the environment. Avoid contact with

skin, eyes and clothing. Wear appropriate personal protective equipment. Protect material from

direct sunlight. Observe good industrial hygiene practices.

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store tightly closed in a dry, cool and well-ventilated place. Keep away from heat, hot surfaces,

sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose

to temperatures exceeding 50 °C/122 °F.

Storage temperature : 10 – 25 °C

7.3. Specific end use(s)

adhesives.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Diphenylmethane diisocyanate, isomers and	homologues (9016-87-9)		
United Kingdom - Occupational Exposure Lin	nits		
Regulatory reference	EH40/2005 (Third edition, 2018). HSE		
o-(p-isocyanatobenzyl)phenyl isocyanate (58	73-54-1)		
United Kingdom - Occupational Exposure Lin	nits		
Regulatory reference	EH40/2005 (Third edition, 2018). HSE		
Exposure limit values for the other componer	nts		
Limestone (1317-65-3)			
United Kingdom - Occupational Exposure Lin	nits		
Local name	Calcium carbonate (Limestone, Marble)		
WEL TWA (OEL TWA)	4 mg/m³ respirable 10 mg/m³ total inhalable		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
zeolites (1318-02-1)			
United Kingdom - Occupational Exposure Lin	nits		
Local name	Aluminium oxides		
WEL TWA (OEL TWA)	10 mg/m³ inhalable dust 4 mg/m³ respirable dust		
Regulatory reference	EH40. HSE		
Calcium carbonate (471-34-1)			
United Kingdom - Occupational Exposure Lin	nits		
Local name	Calcium carbonate		
WEL TWA (OEL TWA)	10 mg/m³ Inhalable fraction		
	4 mg/m³ respirable		
Regulatory reference	EH40. HSE		
Di-"isononyl" phthalate (28553-12-0)			
United Kingdom - Occupational Exposure Lin	nits		
Local name	Diisononyl phthalate		
WEL TWA (OEL TWA)	5 mg/m³		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
8.1.2. Recommended monitoring procedures			
No additional information available			
8.1.3. Air contaminants formed			
No additional information available			
8.1.4. DNEL and PNEC			
4,4'-methylenediphenyl diisocyanate (101-68-	8)		
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	0.1 mg/m³		
Long-term - local effects, inhalation	0.05 mg/m³		
DNEL/DMEL (General population)	-		
Acute - local effects, inhalation	0.05 mg/m³		
Product code: Ford Internal Ref.: 135570	GB - en	Revision date: 8/27/2025	5/12

 Product code: Ford Internal Ref.: 135570
 GB - en
 Revision date: 8/27/2025
 5/12

Long-term - local effects, inhalation	0.025 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	3.7 mg/l
PNEC aqua (marine water)	0.37 mg/l
PNEC aqua (intermittent, freshwater)	37 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	11.7 mg/kg dwt
PNEC sediment (marine water)	1.17 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.33 mg/kg dwt
o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1	1)
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.1 mg/m³
Long-term - local effects, inhalation	0.05 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	0.05 mg/m³
Long-term - local effects, inhalation	0.025 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	3.7 mg/l
PNEC aqua (marine water)	0.37 mg/l
PNEC aqua (intermittent, freshwater)	37 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	11.7
PNEC sediment (marine water)	1.17
PNEC (Soil)	
PNEC soil	2.33 mg/kg dwt
2,2'-methylenediphenyl diisocyanate (2536-05-2)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	0.1 mg/m³
Long-term - local effects, inhalation	0.05 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	0.05 mg/m³
Long-term - local effects, inhalation	0.025 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	3.7 µg/L
PNEC aqua (marine water)	0.37 μg/L
PNEC aqua (intermittent, freshwater)	37 μg/L
PNEC (Sediment)	
PNEC sediment (freshwater)	11.7 mg/kg dwt
PNEC sediment (marine water)	1.17 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.33 mg/kg dwt

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses with side shields. EN 166.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN 14605. EN ISO 13982

Hand protection:

protective gloves. DIN ISO 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust production: dust mask with filter type P2. EN 14387

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Inform appropriate managerial or supervisory personnel of all environmental releases.

Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid Colour : Black. Appearance : Paste.

Odour : Characteristic. Slight.
Odour threshold : Not available
Melting point : Not available
Freezing point : Not available

Boiling point : Not available Flammability : Not flammable Explosive limits : Not applicable Lower explosive limit (LEL) : Not applicable Upper explosive limit (UEL) : Not applicable : > 110 °C (>230 °F) Flash point Auto-ignition temperature : Not applicable Decomposition temperature : > 140 °C (>284°F) рΗ Not available pH solution : Not available Viscosity, kinematic : Not applicable

Viscosity, dynamic : 26 – 32 Pa·s (TE1002-208)

Solubility : Insoluble in: Alcohol. Reacts with water.

Log Kow : Not available
Vapour pressure : Not available
Vapour pressure at 50°C : Not available

Density : 1.7 g/cm³ @ 20 °C (68 °F)

Relative density Not available Relative vapour density at 20°C : Not applicable Particle size : Not available Particle size distribution : Not available : Not available Particle shape : Not available Particle aspect ratio Particle aggregation state : Not available Particle agglomeration state : Not available Particle specific surface area : Not available Particle dustiness : Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with : Water. Alcohol. Amines.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

humidity. Above a temperature of. 250 °C.

10.5. Incompatible materials

Water. Amines. alcohols.

10.6. Hazardous decomposition products

On exposure to high temperature, may decompose, releasing: Isocyanates. Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met

Acute toxicity (dermal) : Based on available data, the classification criteria are not met

Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

Acute toxicity (initialation)	. Based on available data, the classification chieffa are not met
Repair Adhesive Component B	
ATE CLP (dust,mist)	> 5 mg/l
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic
Additional information	skin reaction. : Persons suffering from allergic reactions to isocyanates should avoid contact with the product.
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.
4,4'-methylenediphenyl diisocyanate (101-68-8)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause respiratory irritation.
Diphenylmethane diisocyanate, isomers and homolog	ues (9016-87-9)
STOT-single exposure	May cause respiratory irritation.
4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-single exposure	May cause respiratory irritation.
o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)	
STOT-single exposure	May cause respiratory irritation.
2,2'-methylenediphenyl diisocyanate (2536-05-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Diphenylmethane diisocyanate, isomers and homolog	ues (9016-87-9)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
4,4'-methylenediphenyl diisocyanate (101-68-8)	
STOT-repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).
o-(p-isocyanatobenzyl)phenyl isocyanate (5873-54-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
2,2'-methylenediphenyl diisocyanate (2536-05-2)	·
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Based on available data, the classification criteria are not met
Repair Adhesive Component B	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Potential adverse human health effects and symptoms : Information on Effects: refer to section 4

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

Hazardous to the aquatic environment, short–term (acute)

Hazardous to the aquatic environment, long-term (chronic)

- : The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
- : Based on available data, the classification criteria are not met

: Based on available data, the classification criteria are not met

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Repair Adhesive Component B

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

: Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods

Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not allow to enter drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations

: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Additional information

: Dispose in accordance with all applicable regulations.

European List of Waste (LoW, EC 2000/532)

: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID Not regulated for transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code Applicable on

3(b) Diphenylmethane diisocyanate, isomers and homologues

56(a) 4,4'-methylenediphenyl diisocyanate
56(b) o-(p-isocyanatobenzyl)phenyl isocyanate
56(c) 2,2'-methylenediphenyl diisocyanate

74. 4,4'-methylenediphenyl diisocyanate ; o-(p-isocyanatobenzyl)phenyl isocyanate ; 2,2'-methylenediphenyl diisocyanate

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : 0 %

Other information, restriction and prohibition regulations: Directive 98/24/EC on the protection of the health and safety of workers from the risks related to

chemical agents at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. For details, refer to section 3 and

8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

Section 2. SECTION 4. SECTION 6. SECTION 8. Section 9. SECTION 11. SECTION 12. SECTION 13.

Abbreviations and acronyms

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Bioconcentration factor
BLV Biological limit value

BOD Biochemical oxygen demand (BOD)
COD Chemical oxygen demand (COD)
DMEL Derived Minimal Effect level
DNEL Derived-No Effect Level
EC-No. European Community number
EC50 Median effective concentration

EN European Standard

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Median lethal concentration LD50 Median lethal dose

 LOAEL
 Lowest Observed Adverse Effect Level

 NOAEC
 No-Observed Adverse Effect Concentration

 NOAEL
 No-Observed Adverse Effect Level

NOEC No-Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

OEL Occupational Exposure Limit
PBT Persistent Bioaccumulative Toxic

PNEC Predicted No-Effect Concentration

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS Safety Data Sheet STP Sewage treatment plant

ThOD Theoretical oxygen demand (ThOD)

TLM Median Tolerance Limit

VOC Volatile organic compounds

CAS-No. Chemical Abstract Service number

N.O.S. Not Otherwise Specified

vPvB Very Persistent and Very Bioaccumulative

ED Endocrine disruptor

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of

16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC)

No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation) Acute toxicity (inhal.), Category 4
Carc. 2 Carcinogenicity, Category 2

Eye Irrit. 2 Serious eye damage/eye irritation, Category 2

Resp. Sens. 1 Respiratory sensitisation, Category 1
Skin Irrit. 2 Skin corrosion/irritation, Category 2
Skin Sens. 1 Skin sensitisation, Category 1

STOT RE 2 Specific target organ toxicity – Repeated exposure, Category 2

STOT SE 3 Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Productname: Repair Adhesive Component B

Ford Internal Ref.: 135570 **Revision Date: 27.08.2025**

Involved Products:

Finiscode **Part Number** Packaging

BU7J M2G376 CA 25 ml 1 Part of Kit

> 1 737 528 BU7J M2G376 AA

Repair Adhesive Kit – 2 Component