REAR AXLE OIL SAE 75W-140 C



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ISSUE DATE: 25.11.2014 REVISION DATE: 26.03.2021 SUPERSEDES DATE: 24.04.2017 VERSION: 3.1

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking

 1.1.
 Product identifier

 Trade name
 Rear Axle Oil SAE 75W-140 C

 Product code
 Ford Internal Ref: 190562

 SDS Number
 7666

 Product use
 Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Hydraulic fluids and additives
Uses advised against	No additional information available.

1.3. Details of the supplier of the safety data sheet

Supplier	Distributor
Ford-Werke GmbH	Ford Motor Company Ltd.
Edsel-Ford-Str. 2-14	Parts Distribution Centre
50769 Cologne	Royal Oak Way South
Germany	NN11 8NT Daventry, Northants
+49 221 90-33333	United Kingdom
sdseu@ford.com	+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

2. SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

Supplemental hazard information

EUH208

Contains Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.

EUH210

Safety data sheet available on request.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

3. SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
Dec-1-ene, homopolymer, hydrogenated	68037-01-4 500-183-1 01-2119486452-34- XXXX	10 - < 20	Asp. Tox. 1, H304	
Mineral oil	*	1 - < 10	Asp. Tox. 1, H304	(Note L)
Polysulfides, di-tert-Bu	68937-96-2 273-103-3 01-2119540515-43- XXXX	1-<5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	(46 ≤C < 100) Skin Sens. 1B, H317
Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	N/A 931-384-6 - 01-2119493620-38	1 - < 2,5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	(9.39 ≤C < 100) Skin Sens. 1, H317 (50 <c 100)="" eye<br="" ≤="">Dam. 1, H318 (50 <c 100)="" eye="" irrit.<br="" ≤="">2, H319</c></c>

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

* Contains one or more of the following EC 265-157-1 / RRN 01-2119484627-25, EC 265-169-7 / RRN 01-2119471299-27, EC 265-158-7 / RRN 01-2119487077-29, EC 265-159-2 / RRN 01-2119480132-48

Full text of H-statements: see section 16

4. SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing.
Skin contact:	Wash skin with plenty of water.
Eyes contact	Rinse eyes with water as a precaution.
Ingestion	Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

```
Symptoms/effects after skin contact May cause an allergic skin reaction. May cause moderate irritation.
```

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	Do not attempt to take action without suitable protective equipment. Self- contained breathing apparatus. Complete protective clothing.

6. SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	
Protective equipment	Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the MSDS.
Emergency procedures	Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up.
For emergency responders	
Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	Keep unnecessary personnel away. Ventilate area.
Environmental precautions	Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

	Methods for cleaning up	Large Spills: Stop leak if safe to do so. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Flush residue with large amounts of water. Small spills: Wipe up with absorbent material (for example cloth). Clean surface thoroughly to remove residual contamination.
	Other information	Dispose of materials or solid residues at an authorized site.
6.4.	Reference to other sections	For further information refer to section 13.

7. SECTION 7: Handling and storage

7.1. Precautions for safe handling

6.2.

Precautions for safe handling	Ensure good ventilation of the work station. Wear personal protective equipment.
Handling temperature	70 °C Maximum
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions		Store in a well-ventilated place. Keep cool.	
	Storage temperature	45 °C Maximum	
7.3.	Specific end use(s)	Hydraulic fluids and additives.	

8. SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Contains no substances with occupational exposure limits. **DNEL: Derived no effect level** No data available

(68937-96-2) PNEC: Predicted no effect co No data available Components Polysulfides, di-tert-Bu	Worker Consumer oncentration Type Not applicable	Dermal Inhalation Oral Inhalation Dermal Route Freshwater Seawater Freshwater Sediment sediment	 4.67 mg/kg bodyweight/day 3.29 mg/m³ 0.167 mg/kg bodyweight/day 0.58 mg/m³ 1.67 mg/kg bodyweight/day Value 0.24 µg/L 0.024 µg/L 0.002 mg/l 0.02 mg/kg dut 	Long-term - systemic effects Long-term - systemic effects Long-term - systemic effects Long-term - systemic effects Long-term - systemic effects
(68937-96-2) PNEC: Predicted no effect co No data available Components Polysulfides, di-tert-Bu	Consumer oncentration Type	Inhalation Oral Inhalation Dermal Route Freshwater Seawater Freshwater sediment	3.29 mg/m ³ 0.167 mg/kg bodyweight/day 0.58 mg/m ³ 1.67 mg/kg bodyweight/day Value 0.24 μg/L 0.024 μg/L 0.002 mg/l	Long-term - systemic effect: Long-term - systemic effect: Long-term - systemic effect: Long-term - systemic effect: Form
PNEC: Predicted no effect co No data available Components Polysulfides, di-tert-Bu	oncentration Type	Oral Inhalation Dermal Route Freshwater Seawater Freshwater sediment	0.167 mg/kg bodyweight/day 0.58 mg/m³ 1.67 mg/kg bodyweight/day Value 0.24 µg/L 0.024 µg/L 0.002 mg/l	Long-term - systemic effect Long-term - systemic effect Long-term - systemic effect Form
PNEC: Predicted no effect co No data available Components Polysulfides, di-tert-Bu	oncentration Type	Inhalation Dermal Route Freshwater Seawater Freshwater sediment	0.58 mg/m³ 1.67 mg/kg bodyweight/day Value 0.24 µg/L 0.024 µg/L 0.002 mg/l	Long-term - systemic effect: Long-term - systemic effect: Form
No data available Components Polysulfides, di-tert-Bu	Туре	Dermal Route Freshwater Seawater Freshwater sediment	1.67 mg/kg bodyweight/day Value 0.24 μg/L 0.024 μg/L 0.002 mg/l	Long-term - systemic effects
No data available Components Polysulfides, di-tert-Bu	Туре	Route Freshwater Seawater Freshwater sediment	Value 0.24 μg/L 0.024 μg/L 0.002 mg/l	Form
No data available Components Polysulfides, di-tert-Bu	Туре	Freshwater Seawater Freshwater sediment	0.24 μg/L 0.024 μg/L 0.002 mg/l	
Components Polysulfides, di-tert-Bu		Freshwater Seawater Freshwater sediment	0.24 μg/L 0.024 μg/L 0.002 mg/l	
Polysulfides, di-tert-Bu		Freshwater Seawater Freshwater sediment	0.24 μg/L 0.024 μg/L 0.002 mg/l	
	Not applicable	Seawater Freshwater sediment	0.024 µg/L 0.002 mg/l	Intermittent release
(68937-96-2)		Freshwater sediment	0.024 µg/L 0.002 mg/l	Intermittent release
		Freshwater sediment	0.002 mg/l	Intermittent release
		sediment	•	
		sediment	0.94 mg/kg dwt	Freshwater
			0.094 mg/kg dwt	Seawater
		Soil	18.1 µg/kg dw	
		Oral	6.66 mg/kg food	Secondary Poisoning
		STP	4.51 mg/l	
Exposure controls				
Appropriate engineering con Materials for protective cloth		Ventilation rate enclosures, loc airborne levels been establish Personal prote	ventilation (typically 10 air change es should be matched to condition cal exhaust ventilation, or other en below recommended exposure lin led, maintain airborne levels to an active equipment should be choser ion with the supplier of the protect	s. If applicable, use process gineering controls to maintain mits. If exposure limits have not acceptable level n according to the CEN standards
Individual protection measur	res, such as pe	rsonal protect	ive equipment (PPE)	
Eye protection		Safety glasses	s with side shields. EN 166.	
Skin protection				
Hand protection		application. S	ndation is only valid for the supplie pecial working conditions, like hea he test conditions, can reduce the d glove	t or mechanical strain, which
Material Perme	eation	Thickness (m	m) Comments	
Nitrile rubber (NBR) 6 (> 48	80 minutes)	0.4		Camatril Velours® 730 (Kächele- supply see www.kcl.de) or
In case of splash 6 (> 48 contact: Nitrile rubber (NBR)	80 minutes)	0.4		Camatril Velours® 730 (Kächele supply see www.kcl.de) or
Other protective measur	res	handling the r	ve good personal hygiene measure naterial and before eating, drinking othing and protective equipment to	g, and/or smoking. Routinely
Respiratory protection		If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn		
Device	Filter typ	•		Comments

°C) organic compounds

8.2.

Skin and body protection	Wear suitable protective clothing,Long sleeved protective clothing,EN 14605,EN ISO 13982
Thermal hazard protection	Wear appropriate thermal protective clothing, when necessary.
Environmental exposure controls	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

9. SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

••••	internation on bacie phycical and ener	
	Physical state	Liquid
	Colour	Clear. dark yellow.
	Odour	Sulfur.
	Odour threshold	No data available
	рН	No data available
	Relative evaporation rate (butylacetate=1)	No data available
	Melting point	Not applicable
	Freezing point	No data available
	Boiling point	No data available
	Flash point	> 165 °C (Open cup)
	Auto-ignition temperature	354 °C
	Decomposition temperature	No data available
	Flammability (solid, gas)	Not applicable
	Vapour pressure	No data available
	Relative vapour density at 20 °C	No data available
	Relative density	0.852 – 0.882 @ 15.6°C
	Solubility	insoluble in water.
	Log Pow	No data available
	Viscosity, kinematic	185 mm²/s @ 40°C 25.6 mm²/s @ 100°C
	Viscosity, dynamic	No data available
	Explosive properties	No data available
	Oxidising properties	No data available
	Explosive limits	No data available
9.2.	Other information	
	VOC (EU)	Not applicable
10. S	ECTION 10: Stability and reactivity	
10.1.	Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
10.2.	Chemical stability	Stable under normal conditions.
10.3.	Possibility of hazardous reactions	No dangerous reactions known under normal conditions of use.
10.4.	Conditions to avoid	None under recommended storage and handling conditions (see section 7).
10.5.	Incompatible materials	No additional information available.

10.6. Hazardous decomposition products

Thermal decomposition generates : Sulphur oxides. Carbon dioxide. Carbon monoxide. fume.

11. SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity			Based on available data, the classification criteria are not met.					
Mixture								
Name	Method	Туре	Exposure route	Value	Unit	Species	Remarks	
Rear Axle Oil SAE 75W- 140 C		ATE	oral	> 5000	mg/kg		(calculated value)	
Substance								
Name	Method	Туре	Exposure route	Value	Unit	Species	Remarks	
Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)		ATE	oral	500	mg/kg			
Skin corrosion/irritation	n		Based on available	data, the c	lassificatio	n criteria are n	ot met.	
Serious eye damage/irr	ritation		Based on available	data, the c	lassificatio	n criteria are n	ot met.	
Respiratory or skin sen	sitisation		Based on available	data, the c	lassificatio	n criteria are n	ot met.	
Germ cell mutagenicity	,		Based on available	data, the c	lassificatio	n criteria are n	ot met	
Carcinogenicity			Based on available	data, the c	lassificatio	n criteria are n	ot met	
Reproductive toxicity			Based on available	data, the c	lassificatio	n criteria are n	ot met	
STOT-single exposure			Based on available	data, the c	lassificatio	n criteria are n	ot met	
STOT-repeated exposu	re		Based on available	data, the c	lassificatio	n criteria are n	ot met	
Aspiration hazard			Based on available	data the c	lassificatio	n criteria are n	ot met	

12. SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Hazardous to the aquatic environment, short-term (acute)

Substance / Product	Trophic level	Species	Туре	Value	Duration	Remarks	
Polysulfides, di-tert-Bu (68937-96-2)	aquatic invertebrates	Daphnia magna	EC50	> 0,27 mę	g/L 48 h		
	algae	algae	EC50	0,838 mg	/L 72 h		
Reaction products of bis(4-methylpentan-2- yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)	Fish	Fish	LC50	~ 8,5 mg/	'L 96 h		
Hazardous to the aquat	tic environment,	long-term (cł	nronic)				
Substance / Product	Trophic level	Species	Туре	Value	Duration	Remarks	
Reaction products of bis(4-methylpentan-2-	crustacea	Daphnia magna	NOEC	0,12 mg/l	21 d		
yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)	algae	algae	NOEC	1,7 mg/l	96 h		
day Fard Internal Dafe 100560							0/14

12.2. Persistence and degradability

	• •						
	Polysulfides, di-tert-Bu (68937-96-2)						
	Biodegradation	13 % (28 d, OECD TG 301 B)					
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)						
	Biodegradation	7.4 % (28 d, OECD TG 301 B)					
2.3.	Bioaccumulative potential						
	Dec-1-ene, homopolymer, hydrogenated (68037-01-4)						
	Log Pow	> 3					
	Log Kow	> 6.5					
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)						
	Log Kow	> 6.5 measured					
2.4.	Mobility in soil						
	No additional information available.						
2.5.	Results of PBT and vPvB assessment						
	Rear Axle Oil SAE 75W-140 C						
	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.						
	This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.						
2.6.	Other adverse effects						
	No additional information available.						
13. SI	ECTION 13: Disposal consideratio	ns					
13.1.	Waste treatment methods						
	Regional legislation (waste)	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.					
	Waste treatment methods	Dispose of contents/container in accordance with licensed collector's sorting instructions. Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not allow to enter drains or water courses.					
	Additional information	Avoid discharge into drains, water courses or onto the ground.					
	European List of Waste (LoW) code						
	13 02 06* 15 01 10*	synthetic engine, gear and lubricating oils					
	15 01 10*	packaging containing residues of or contaminated by dangerous substances					
		5					

14. SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID Not regulated for transport

15. SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006

	Rear Axle Oil SAE 75W-140 C ; Dec-1-ene, homopolymer, hydrogenated ; Polysulfides, di-tert-Bu ; Mineral oil ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10		
	Polysulfides, di-tert-Bu ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1		
	Contains no substance on the REACH candidate list			
	Contains no REACH Annex XIV substances			
	VOC (EU)	Not applicable		
	Other information, restriction and prohibition regulations	Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.		
	Seveso Information	Not applicable.		
	National regulations			
	No additional information available.			
15.2.	Chemical safety assessment			

No chemical safety assessment has been carried out

16. SECTION 16: Other information

General.	
Abbreviations and	acronyms
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AGW	Occupational exposure limit value
ATE	Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM	Federal Institute for Materials Research and Testing, Germany
BAT	Maximum permissible concentration of biological working substances.
BCF	Bio-concentration factor.
BLV	Biological limit values
BLV	Biological limit values (BGW, Austria)
BMGV	Biological Monitoring Guidance Value (EH40,UK).
BOD5	Biochemical oxygen demand within 5 days
BOD	Biochemical oxygen demand
bw	Body weight.
calcd.	Calculated
CAS	Chemical Abstract Service.
CEN	European Committee for Standardization
CESIO	European Committee on Organic Surfactants and their Intermediates.
COD	Chemical oxygen demand
CLP	Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
CMR	Carcinogenic, Mutagenic or Reproduction Toxic Substances

CSA	Chemical safety assessment
CSR	Chemical Safety Report.
DMEL	Derived Minimum Effect Level.
DNEL	Derived no effect level
EAC	European waste catalogue
EC	European community
EC50	Effective concentration
EINECS	European Inventory of Existing Commercial Chemical Substances.
ELINCS	European List of Notified Chemical Substances.
EN	European norm.
ERC	ERC (Environmental Release category)
EU	European Union
GLP	Good Laboratory Practice.
GHS	Globally Harmonized System of Classification and Labeling of Chemicals.
GW/VL	Occupational exposure limit value.
GW-kw/VL-cd	Occupational exposure limit value - short term.
GW-M/VL-M	Occupational exposure limit value – "Ceiling".
IATA	International Air Transport Association
IBC code	International Bulk Chemical (Code) (International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk).
ICAO	International Civil Aviation Organization
IC50	Inhibition Concentration 50%.
IECSC	Inventory of Existing Chemical Substances in China.
IMDG	International Maritime Dangerous Goods
ISO	International Standards Organization.
IUPAC	International Union of Pure and Applied Chemistry
LC50	Lethal Concentration 50%.
LCLo	Lowest published lethal concentration.
LD50	Lethal Dose 50%.
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest observable effect concentration.
LOEL	Lowest observable effect level.
LQ	Limited quantities
TRK-Kzw	Threshold limit value - Short-term exposure limit / Technical reference concentration - short- time value, Austria.
MAK-Mow	Maximum allowable workplace concentration – instantaneous value, Austria.
MAK-Tmw, TRK-Tmw	Maximum allowable workplace concentration – daily mean value / Technical standard concentration – daily mean value, Austria.
MAK	Threshold limit values Germany.
MARPOL	International Convention for the Prevention of Pollution from Ships.
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
NOEL	no-observed-effect level
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limits
PBT	Persistent Bioaccumulative Toxic
code: Ford Internal Ref: 190562	GP on Povision date: 3/26/2021 0/1

PC (Chemical product category)	PC (Chemical product category)
PNEC	Predicted No-Effect Concentration
POCP	Photochemical ozone creation potential.
POP	Persistent Organic Pollutants
PPE	Personal protective equipment
Process category	Process category
REACH	Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL	Specific concentration limit.
STEL	Short-term Exposure Limit
STP	Sewage treatment plant
SU (Sector of use)	SU (Sector of use)
SVHC	Substance of Very High Concern.
TLV	Threshold Limit Value
TRGS	Technical Rules for Hazardous Substances (German Standard).
TWA	Time Weighted Average
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
VbF	Ordinance on Flammable Liquids, Austria
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative
WEL-TWA	Workplace Exposure Limit-Long term exposure limit (8-hour TWA(=time weighted average)reference period).
WEL-STEL	Workplace Exposure Limit-Short term exposure limit (15-minute reference period).
Full text of H- and EUH-stater	nents
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4.
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2.
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3.
Asp. Tox. 1	Aspiration hazard, Category 1.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2.
Skin Sens. 1	Skin sensitisation, Category 1.
Skin Sens. 1B	Skin sensitisation, category 1B.
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH208	Contains Polysulfides, di-tert-Bu, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.
EUH210	Safety data sheet available on request

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name:

Ford Int. Ref. No.:

REVISION DATE: 26.03.2021

Involved Products:

.

Finiscode	Part n
1 1 836 674	7U7J

Part number 7U7J M2C192 AB

190562

Rear Axle Oil SAE 75W-140 C

Container Size: