



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 03.07.2018

REVISION DATE: 14.05.2025

SUPERSEDES: 02.05.2022

VERSION: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Adhesive L-HY 2
Product code	: Ford Internal Ref.: 199777
SDS Number	: 3039
Unique Formula Identifier (UFI)	: GR6S-PJQJ-RU1U-NA73
Product use	: Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category	: Adhesives, sealants
--------------------------	-----------------------

1.2.2. Uses advised against

Restrictions on use	: No additional information available.
---------------------	--

1.3. Details of the supplier of the safety data sheet

Supplier

Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor

Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Health hazards	Skin corrosion/irritation, Category 2 Serious eye damage/eye irritation, Category 2 Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H315 H319 H335	Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.
Environmental hazards	Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word

Warning

Contains

1,6-hexanediyl bismethacrylate

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P261	Avoid breathing vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves, eye protection.

Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337+P313	If eye irritation persists: Get medical advice/attention.

EUH-statements

EUH208 - Contains 3,4,5,6-tetrahydrophthalic anhydride, Methyl methacrylate. May produce an allergic reaction.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
1,6-hexanediyl bismethacrylate	6606-59-3 229-551-7 01-2120760621-59-XXXX	50 – 100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412	
3,4,5,6-tetrahydrophthalic anhydride	2426-02-0 219-374-3 607-099-00-5	0.1 - < 1	Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Chronic 3, H412	(Note C)
Methyl methacrylate	80-62-6 201-297-1 607-035-00-6 01-2119452498-28-XXXX	0,1 - < 1	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317	# (Note D)

Comments

: #: substance with a Community workplace exposure limit

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D - Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash off with soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Drink plenty of water. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects:	: May produce an allergic reaction.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
Symptoms/effects after skin contact	: Causes skin irritation. Redness. Skin rash/inflammation.
Symptoms/effects after eye contact	: Causes serious eye irritation. Conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Carbon dioxide. Dry powder.
Unsuitable extinguishing media	: Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO ₂). Nitrous oxide.
--	--

5.3. Advice for firefighters

Firefighting instructions	: On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray. Move containers from fire area if it can be done without personal risk. In case of fire and/or explosion do not breathe fumes.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep unnecessary personnel away.
------------------	------------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: For personal protection, see section 8 of the SDS.
Emergency procedures	: Ventilate spillage area. Avoid breathing vapours. Avoid contact with skin and eyes. Keep away from sources of ignition.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 :" Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Ensure that enough fresh air is supplied to dilute and remove dusts, fumes or vapours. Between 5 and 15 air changes per hour are recommended, with a through draught.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Incompatible products	: Strong oxidizing agent. Strong bases. Acids. reducing materials.
Storage area	: Keep cool. Protect from sunlight. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
Special rules on packaging	: Keep only in original container.

7.3. Specific end use(s)

adhesives.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Methyl methacrylate (80-62-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Methyl methacrylate
IOEL TWA	50 ppm
IOEL STEL	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU

United Kingdom - Occupational Exposure Limits

Local name	Methyl methacrylate
WEL TWA (OEL TWA)	208 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	416 mg/m ³
	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

1,6-hexanediyi bismethacrylate (6606-59-3)

DNEL/DMEL (Workers)

Acute - systemic effects, inhalation 4.2 mg/kg bw/day

Long-term - systemic effects, inhalation 14.5 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 2.5 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 4.3 mg/m³

Long-term - local effects, dermal 2.5 mg/kg bw/day

PNEC (Water)

PNEC aqua (freshwater) 4.88 µg/L

PNEC aqua (marine water) 0.488 µg/L

PNEC aqua (intermittent, freshwater) 45 µg/L

PNEC (Sediment)

PNEC sediment (freshwater) 0.262 mg/kg dwt

PNEC sediment (marine water) 0.0262 mg/kg dwt

PNEC (Soil)

PNEC soil 0.05 µg/kg dw

PNEC (STP)

PNEC sewage treatment plant 800 mg/l

Methyl methacrylate (80-62-6)

DNEL/DMEL (Workers)

Acute - local effects, dermal 1.5 mg/cm²

Long-term - systemic effects, dermal 13.67 mg/kg bw/day

Long-term - local effects, dermal 1.5 mg/cm²

Long-term - systemic effects, inhalation 208 mg/m³

Long-term - local effects, inhalation 208 mg/m³

DNEL/DMEL (General population)

Acute - local effects, dermal 1.5 mg/cm²

Long-term - systemic effects, inhalation 74.3 mg/m³

Long-term - systemic effects, dermal 8.2 mg/kg bw/day

Long-term - local effects, dermal 1.5 mg/cm²

Long-term - local effects, inhalation 104 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0.94 mg/l

PNEC aqua (marine water) 0.94 mg/l

PNEC aqua (intermittent, freshwater) 0.94 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 5.74 mg/kg dwt

PNEC (Soil)

PNEC soil 1.47 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 10 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls**8.2.1. Appropriate engineering controls****Appropriate engineering controls:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment**Personal protective equipment:**

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection**Eye protection:**

Safety glasses with side shields. EN 166.

8.2.2.2. Skin protection**Skin and body protection:**

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment. EN 14605. EN ISO 13982

Hand protection:

The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove. DIN ISO 374. protective gloves

Material	Permeation	Thickness (mm)	Comments
Butyl rubber	6 (> 480 minutes)	0.7	Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Butyl rubber	6 (> 480 minutes)	0.7	Glove recommendation: Butoject® 898 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection**Materials for protective clothing:**

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection**Respiratory protection:**

Type A - High-boiling (>65 °C) organic compounds

8.2.2.4. Thermal hazards**Thermal hazard protection:**

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls**Environmental exposure controls:**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

Consumer exposure controls:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: colourless to slightly yellow.
Appearance	: Liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: < -25 °C
Boiling point	: > 315 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 150 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: 1 – 30 mPa·s
Solubility	: Not available
Log K _{ow}	: Not available
Vapour pressure	: > 1
Vapour pressure at 50°C	: Not available
Density	: 0.98 – 1.1 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 3 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Can react with. Strong bases. Strong acids, strong oxidants. reducing materials.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Avoid contact with hot surfaces.

10.5. Incompatible materials

Acids. Reducing agents. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

During fire, gases hazardous to health may be formed. Carbon oxides (CO, CO₂). Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Based on available data, the classification criteria are not met
Acute toxicity (dermal)	: Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met

Methyl methacrylate (80-62-6)

IARC group	3 - Not classifiable
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause respiratory irritation.

1,6-hexanediyl bismethacrylate (6606-59-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Methyl methacrylate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Based on available data, the classification criteria are not met
Aspiration hazard	: Based on available data, the classification criteria are not met

Adhesive L-HY 2

Viscosity, kinematic	> 20.5 mm ² /s
----------------------	---------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information

Potential adverse human health effects and symptoms	: Prolonged inhalation may be harmful, Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
---	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Based on available data, the classification criteria are not met
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

1,6-hexanediyl bismethacrylate (6606-59-3)

LC50 - Fish [1]	4.5 mg/l
EC50 72h - Algae [1]	5.33 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1,6-hexanediyl bismethacrylate (6606-59-3)

Log Pow	> 4
---------	-----

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Adhesive L-HY 2

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Container under pressure. Do not drill or burn even after use.

European List of Waste (LoW, EC 2000/532) : The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Not regulated for transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	Methyl methacrylate
3(b)	Adhesive L-HY 2 ; 1,6-hexanediyl bismethacrylate ; Methyl methacrylate
3(c)	Adhesive L-HY 2 ; 1,6-hexanediyl bismethacrylate
Contains no substance(s) listed on the REACH Candidate List	
Contains no substance(s) listed on REACH Annex XIV (Authorisation List)	
Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)	
Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)	
VOC content	: < 3 %
Other information, restriction and prohibition regulations :	Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

SECTION 1 : UFI. SECTION 3. Information on ingredients. Label elements.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN	REACH Registration no.
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
VOC	Volatile organic compounds
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 3,4,5,6-tetrahydrophthalic anhydride, Methyl methacrylate. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H335	Calculation method
Aquatic Chronic 3	H412	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Productname: Adhesive L-HY 2

Ford Internal Ref.: 199777

Revision Date: 14.05.2025

Involved Products:

Finiscode	Part Number	Packaging	Part of Kit		
1	JU7J M2G402 CA	1 g	2 843 579	SU7J M2G402 AA	Hybrid Adhesive Kit