

# TRANSMISSION FLUID 75W S-FVA



## SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 26.01.2022  
REVISION DATE: 19.05.2025  
SUPERSEDES: 13.01.2025  
VERSION: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Transmission Fluid 75W S-FVA  
Product code : Ford Internal Ref.: 505862  
SDS Number : 9310  
Product use : Professional use

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Function or use category : Transmission Oil

##### 1.2.2. Uses advised against

Restrictions on use : None known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Ford-Werke GmbH  
Edsel-Ford-Str. 2-14  
50769 Cologne  
Germany  
+49 221 90-33333  
sdseu@ford.com

##### Distributor

Ford Motor Company Ltd.  
Parts Distribution Centre  
Royal Oak Way South  
NN11 8NT Daventry, Northants  
United Kingdom  
+44 1327 305 198

#### 1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Environmental hazards	Hazardous to the aquatic environment – H412 Chronic Hazard, Category 3	Harmful to aquatic life with long lasting effects.
-----------------------	---	--

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Signal word -

##### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

##### Prevention

## EUH-statements

EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.

**2.3. Other hazards**

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-XXXX	70 - 80	Asp. Tox. 1, H304	(Note L)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29-XXXX	10 - 20	Asp. Tox. 1, H304	(Note L)
2,2 <sup>t</sup> -(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	1218787-32-6 620-540-6 01-2119510877-33-XXXX	0,25 - < 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1.0)	(5 ≤ C < 100) Skin Corr. 1C; H314
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	N/A 931-384-6 01-2119493620-38-XXXX	0,1 - < 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	(9.39 ≤ C < 100) Skin Sens. 1; H317 (50 < C ≤ 100) Eye Irrit. 2; H319

Note L - The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

**SECTION 4: First aid measures****4.1. Description of first aid measures**

First-aid measures general

: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

First-aid measures after skin contact

: Take off immediately all contaminated clothing and wash it before reuse. Wash immediately with plenty of water. Get medical advice/attention.

- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
- First-aid measures after ingestion : Do not induce vomiting. Rinse mouth thoroughly. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : Contact can lead to symptoms of oil acne / folliculitis. May produce an allergic reaction.
- Symptoms/effects after ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam. Water spray. For small fire: Dry chemical, soda ash, lime or sand. carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : Organic compounds. smokes. Various hydrocarbon fragments. Carbon monoxide.

#### 5.3. Advice for firefighters

- Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the MSDS.
- Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up.

##### 6.1.2. For emergency responders

- Protective equipment : Wear recommended personal protective equipment. For personal protection, see section 8 of the SDS.
- Emergency procedures : Keep unnecessary personnel away. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak without risks if possible. Move containers from fire area if it can be done without personal risk.
- Methods for cleaning up : Large Spills: Stop leak if safe to do so. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Avoid contact with skin, eyes and clothing.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ensure adequate ventilation, especially in confined areas.
- Storage conditions : Store locked up. Store in a dry, cool and well-ventilated place.
- Incompatible materials : Avoid PVC.
- Packaging materials : Polyethylene (high density). Mild steel.

### 7.3. Specific end use(s)

Transmission Oil.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

No additional information available

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

### 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)

---

#### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 0.3 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 2.112 mg/m<sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral 0.214 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 0.745 mg/m<sup>3</sup>

Long-term - systemic effects, dermal 0.214 mg/kg bodyweight/day

#### PNEC (Water)

PNEC aqua (freshwater) 0.214 µg/L

PNEC aqua (marine water) 0.021 µg/L

PNEC aqua (intermittent, freshwater) 0.87 µg/L

#### PNEC (Sediment)

PNEC sediment (freshwater) 1.692 mg/kg dwt

PNEC sediment (marine water) 0.169 mg/kg dwt

#### PNEC (Soil)

PNEC soil 5 mg/kg dwt

**PNEC (Oral)**

PNEC oral (secondary poisoning) 2 mg/kg food

**PNEC (STP)**

PNEC sewage treatment plant 1500 µg/L

**Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)**

---

**DNEL/DMEL (Workers)**

Acute - local effects, dermal 160 µg/cm<sup>2</sup>  
Long-term - systemic effects, dermal 12.5 mg/kg bodyweight/day  
Long-term - local effects, dermal 160 µg/cm<sup>2</sup>  
Long-term - systemic effects, inhalation 4.28 mg/m<sup>3</sup>

**DNEL/DMEL (General population)**

Acute - local effects, dermal 160 µg/cm<sup>2</sup>  
Long-term - systemic effects, oral 0.25 mg/kg bodyweight/day  
Long-term - systemic effects, inhalation 1.09 mg/m<sup>3</sup>  
Long-term - systemic effects, dermal 6.25 mg/kg bodyweight/day  
Long-term - local effects, dermal 160 µg/cm<sup>2</sup>

**PNEC (Water)**

PNEC aqua (freshwater) 2.4 µg/L  
PNEC aqua (marine water) 0.24 µg/L  
PNEC aqua (intermittent, freshwater) 150 µg/L  
PNEC aqua (intermittent, marine water) 15 µg/L

**PNEC (Sediment)**

PNEC sediment (freshwater) 12.9 µg/kg dw  
PNEC sediment (marine water) 1.29 µg/kg dw

**PNEC (Soil)**

PNEC soil 1.17 µg/kg dw

**PNEC (Oral)**

PNEC oral (secondary poisoning) 10 mg/kg food

**PNEC (STP)**

PNEC sewage treatment plant 24.33 mg/l

**Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**

---

**DNEL/DMEL (Workers)**

Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day  
Long-term - systemic effects, inhalation 2.73 mg/m<sup>3</sup>  
Long-term - local effects, inhalation 5.58 mg/m<sup>3</sup>

**DNEL/DMEL (General population)**

Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day

**PNEC (Oral)**

PNEC oral (secondary poisoning) 9.33 mg/kg food

**8.1.5. Control banding**

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses with side shields. EN 166.

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing. Long sleeved protective clothing. EN 14605. EN ISO 13982

##### Hand protection:

Protective gloves. ISO 374-1. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see <a href="http://www.kcl.de">www.kcl.de</a> ) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see <a href="http://www.kcl.de">www.kcl.de</a> ) or comparable product.

#### Other skin protection

##### Materials for protective clothing:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Type A - High-boiling (>65 °C) organic compounds

#### 8.2.2.4. Thermal hazards

##### Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Odour	: Slight hydrocarbon.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 200 °C (estimated value)
Flammability	: Not available

Explosive limits	: Not available
Lower explosive limit (LEL)	: 1 vol %
Upper explosive limit (UEL)	: 10 vol %
Flash point	: 208 °C ASTM D92
Auto-ignition temperature	: 320 °C
Decomposition temperature	: Not available
Pour point	: -51 °C ASTM D97
pH	: Not applicable
Viscosity, kinematic	: 27.6 mm <sup>2</sup> /s @40°C ASTM D445
Solubility	: insoluble in water.
Log Kow	: Not available
Log Pow	: > 6 Data from similar product
Vapour pressure	: < 0.5 hPa (estimated value)
Vapour pressure at 50°C	: Not available
Density	: 851 kg/m <sup>3</sup> @15°C ASTM D4052
Relative density	: 0.851 @15°C
Relative vapour density at 20°C	: > 1 (estimated value)
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

### 9.2.2. Other safety characteristics

VOC content : Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid high temperatures. Direct sunlight.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Oxidising agents.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Based on available data, the classification criteria are not met
Acute toxicity (dermal)	: Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met

<b>2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)</b>	
ATE CLP (oral)	500 mg/kg bodyweight
<b>Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)</b>	
LD50 oral	300 – 2000 mg/kg
ATE CLP (oral)	500 mg/kg bodyweight

Skin corrosion/irritation	: Based on available data, the classification criteria are not met pH: Not applicable
Serious eye damage/irritation	: Based on available data, the classification criteria are not met pH: Not applicable
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met All hydrocarbons in this mixture: Note L is applicable (DMSO <3%), therefore no classification as carcinogen
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Based on available data, the classification criteria are not met
Aspiration hazard	: Based on available data, the classification criteria are not met

<b>Transmission Fluid 75W S-FVA</b>	
Viscosity, kinematic	27.6 mm <sup>2</sup> /s @40°C ASTM D445

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

### 11.2.2. Other information

Potential adverse human health effects and symptoms : Exposure may produce an allergic reaction, Information on Effects: refer to section 4

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Based on available data, the classification criteria are not met

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

### 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)

LC50 - Fish [1]	0.1 mg/l
EC50 - Crustacea [1]	0.043 ml/l

### 12.2. Persistence and degradability

#### 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)

Persistence and degradability	Readily biodegradable. (OECD 301D method).
Biodegradation	63 % (28 d, OECD 301D)

#### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)

Biodegradation	7.4 % (28 d, OECD TG 301 B)
----------------	-----------------------------

### 12.3. Bioaccumulative potential

#### Transmission Fluid 75W S-FVA

Log Pow	> 6 Data from similar product
---------	-------------------------------

#### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)

Log Kow	> 6.5 measured
---------	----------------

## 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

### Transmission Fluid 75W S-FVA

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Regional waste regulation : Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.
- Waste treatment methods : Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not allow to enter drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
- European List of Waste (LoW, EC 2000/532) : The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
13 02 06\* - synthetic engine, gear and lubricating oils  
15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID  
Not regulated for transport

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(b)	2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) ; Distillates (petroleum), hydrotreated light paraffinic ; Distillates (petroleum), hydrotreated heavy paraffinic
3(c)	Transmission Fluid 75W S-FVA ; 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : Not applicable

Other information, restriction and prohibition regulations : Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.

## Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Indication of changes:

General.

### Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
STEL	Short-term Exposure Limit
VOC	Volatile organic compounds
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
OEL	Occupational Exposure Limit
RRN	REACH Registration no.
TWA	Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour workday.

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

### Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C

Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]**

Aquatic Chronic 3                      H412                      Calculation method

*The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.*

# Attachment to the Safety Data Sheet



Productname: Transmission Fluid 75W S-FVA

Ford Internal Ref.: 505862

Revision Date: 19.05.2025

---

## Involved Products:

	<b>Finiscode</b>	<b>Part Number</b>	<b>Packaging</b>
1	2 610 494	MU7J 7J106 AA	1 l
2	2 849 446	SU7J 7J106 AA	1 l