SEALANT DB-MS

(Ford)

SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 02.06.2025 REVISION DATE: 02.06.2025

VERSION: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Sealant DB-MS

Product code : Ford Internal Ref.: 516070

SDS Number : 12741

Unique Formula Identifier (UFI) : 6X73-XG6X-V106-2EG0
Product use : Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Adhesives, sealants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier Distributor

Ford-Werke GmbH Ford Motor Company Ltd.
Edsel-Ford-Str. 2-14 Parts Distribution Centre
50769 Cologne Royal Oak Way South
Germany NN11 8NT Daventry, Northants
+49 221 90-33333 United Kingdom

+49 221 90-33333 United Kingdom sdseu@ford.com +44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Health hazards Skin sensitisation, Category 1 H317 May cause an allergic skin reaction.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word Warning

Contains

Trimethoxyvinylsilane; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Prevention

P280 Wear protective gloves.

Response

P332+P313 If skin irritation occurs: Get medical advice/attention.

2.3. Other hazards

Other hazards which do not result in classification : In contact with moisture, the product liberates methanol.

When using the product, up to 2% of methanol can be released.

Methanol: Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled.

Damages the organs.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Trimethoxyvinylsilane	2768-02-7 220-44-8 014-049-00-0 01-2119513215-52-XXXX	1-<2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 (ATE=4500 ppmv/4h) Skin Sens. 1B, H317	
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	68610-51-5 271-867-2 - 01-2119496062-39	0,1 - < 1	Repr. 2, H361 Aquatic Chronic 4, H413	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 - 01-2119491304-40-XXXX	0,01 - < 0,1	Skin Sens. 1A, H317 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 1, H410	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash immediately with

plenty of water. Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes

minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician

immediately.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth thoroughly. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard firefighting

procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up. Use personal protection

recommended in Section 8 of the MSDS.

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and

clothing. Local authorities should be advised if significant spillages cannot be contained. Wear

appropriate protective equipment and clothing during clean-up.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. For personal protection, see section 8 of the

SDS.

Emergency procedures : Keep unnecessary personnel away. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Move containers from fire area if it can be done without personal

risk.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the

environment. Avoid contact with skin, eyes and clothing.

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ensure adequate ventilation, especially in confined areas.

Storage conditions : Store locked up. Store in a dry, cool and well-ventilated place.

 Product code: Ford Internal Ref.: 516070
 GB - en
 Revision date: 6/2/2025
 3/10

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Exposure limit values for the other components					
Methanol (67-56-1)					
EU - Indicative Occupational Exposure Limit (IOEL)					
Local name	Methanol				
IOEL TWA	260 mg/m³				
	200 ppm				
Remark	Skin				
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC				
United Kingdom - Occupational Exposure Limits					
Local name	Methanol				
WEL TWA (OEL TWA)	266 mg/m³				
	200 ppm				
WEL STEL (OEL STEL)	333 mg/m³				
	250 ppm				
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)				
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE				
8.1.2. Recommended monitoring procedures					
No additional information available					
8.1.3. Air contaminants formed					
No additional information available					
8.1.4. DNEL and PNEC					
Trimethoxyvinylsilane (2768-02-7)					
DNEL/DMEL (Workers)					
Long-term - systemic effects, dermal	3.9 mg/kg bodyweight/day				
Long-term - systemic effects, inhalation	27.6 mg/m³				
DNEL/DMEL (General population)					
Long-term - systemic effects,oral	0.3 mg/kg bodyweight/day				
Long-term - systemic effects, inhalation	18.9 mg/m³				
Long-term - systemic effects, dermal	7.8 mg/kg bodyweight/day				
PNEC (Water)					

PNEC (Sediment)

PNEC aqua (freshwater)

PNEC aqua (marine water)

PNEC aqua (intermittent, freshwater)

PNEC sediment (freshwater) 1.5 mg/kg dwt

0.4 mg/l

0.04 mg/l

2.4 mg/l

PNEC sediment (marine water) 0.15 mg/kg dwt

PNEC (Soil)

PNEC soil 0.06 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 6.6 mg/l

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 0.5 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 0.68 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 0.05 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 0.17 mg/m³

Long-term - systemic effects, dermal 0.25 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater) 0.002 mg/l

PNEC aqua (marine water) 0 mg/l

PNEC aqua (intermittent, freshwater) 0.009 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 0.11 mg/kg dwt

PNEC (Soil)

PNEC soil 0.21 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 1 mg/l

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)

PNEC (Water)

PNEC aqua (freshwater)

PNEC aqua (marine water)

PNEC aqua (intermittent, freshwater)

PNEC aqua (intermittent, marine water)

0.002 mg/l

PNEC aqua (intermittent, marine water)

0.002 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 426.26 mg/kg KW
PNEC sediment (marine water) 85.25 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 100 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses with side shields. EN 166.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. Long sleeved protective clothing. EN 14605. EN ISO 13982

Hand protection:

Protective gloves. DIN ISO 374. The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment

8.2.2.3. Respiratory protection

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Black.
Appearance	:	Pasty.
Odour	:	Characteristic.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosive limit (LEL)	:	0.4 vol %
Upper explosive limit (UEL)	:	2.9 vol %
Flash point	:	> 100 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not applicable.

Viscosity, kinematic : Not available Solubility insoluble in water. Log Kow Not available Vapour pressure 15 hPa Vapour pressure at 50°C : Not available : 1.4 g/cm3 @20°C Density Relative density : Not available : Not available Relative vapour density at 20°C Not applicable Particle size Particle size distribution : Not applicable Particle shape : Not applicable Particle aspect ratio : Not applicable Particle aggregation state Not applicable Particle agglomeration state : Not applicable Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. In contact with moisture, the product liberates methanol.

When using the product, up to 2% of methanol can be released.

Methanol: Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled. Damages the organs.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat and sources of ignition. Prevent moisture contact.

10.5. Incompatible materials

Acids. Strong oxidizers. water.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

Trimethoxyvinylsilane (2768-02-7)		
LC50 Inhalation - Rat [ppm]	2773 ppm	
LC50 Inhalation - Rat (Vapours)	16.8 mg/l/4h	

Skin corrosion/irritation : Based on available data, the classification criteria are not met

pH: Not applicable.

Serious eye damage/irritation : Based on available data, the classification criteria are not met

pH: Not applicable.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Based on available data, the classification criteria are not met Carcinogenicity : Based on available data, the classification criteria are not met Reproductive toxicity : Based on available data, the classification criteria are not met STOT-single exposure : Based on available data, the classification criteria are not met STOT-repeated exposure : Based on available data, the classification criteria are not met Aspiration hazard : Based on available data, the classification criteria are not met

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information

Potential adverse human health effects and symptoms : Exposure may produce an allergic reaction, Information on Effects: refer to section 4

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

Based on available data, the classification criteria are not met
 Based on available data, the classification criteria are not met

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Trimethoxyvinylsilane (2768-02-7)

Log Kow 1.1

Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene (68610-51-5)

Log Pow 7.93 @ 25°C

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Sealant DB-MS

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

: Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods : Collect and reclaim or dispose in closed containers at licensed waste disposal site. Do not

contaminate ponds, waterways or ditches with chemical or used container. Do not allow to enter drains or water courses. Dispose of contents/container in accordance with licensed collector's

sorting instructions.

European List of Waste (LoW, EC 2000/532) : The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

15 01 02 - plastic packaging

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID Not regulated for transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code Applicable on 3(a) Trimethoxyvinylsilane

3(b) Sealant DB-MS; Trimethoxyvinylsilane; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl

1,2,2,6,6-pentamethyl-4-piperidyl sebacate

3(c) Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

VOC content : Not applicable.

Other information, restriction and prohibition regulations: Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on

the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

STEL Short-term Exposure Limit
VOC Volatile organic compounds
ATE Acute Toxicity Estimate
BCF Bioconcentration factor

CLP Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DMEL Derived Minimal Effect level
DNEL Derived-No Effect Level
EC50 Median effective concentration

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Median lethal concentration

LD50 Median lethal dose

LOAEL Lowest Observed Adverse Effect Level
NOAEC No-Observed Adverse Effect Concentration

NOAEL No-Observed Adverse Effect Level
NOEC No-Observed Effect Concentration
PBT Persistent Bioaccumulative Toxic
PNEC Predicted No-Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

SDS Safety Data Sheet
STP Sewage treatment plant
TLM Median Tolerance Limit

vPvB Very Persistent and Very Bioaccumulative

OEL Occupational Exposure Limit RRN REACH Registration no.

TWA Time Weighted Average. The average concentration of a chemical in air over the total exposure time-usually an 8-hour

workday.

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of

16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC)

No 1907/2006.

Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation) Acute toxicity (inhal.), Category 4

Aquatic Acute 1 Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1 Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 4 Hazardous to the aquatic environment – Chronic Hazard, Category 4

Flam. Liq. 3 Flammable liquids, Category 3 Repr. 1B Reproductive toxicity, Category 1B Repr. 2 Reproductive toxicity, Category 2 Skin Sens. 1 Skin sensitisation, Category 1 Skin Sens. 1A Skin sensitisation, category 1A Skin Sens. 1B Skin sensitisation, category 1B H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.
H360F May damage fertility.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Skin Sens. 1 H317 Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Productname: Sealant DB-MS

Ford Internal Ref.: 516070 Revision Date: 02.06.2025

Involved Products:

 Finiscode
 Part Number
 Packaging

 1
 2 819 932
 RU7J 4G9105 AA
 50 g